



US00D737756S

(12) **United States Design Patent**
Mathonet et al.

(10) **Patent No.:** **US D737,756 S**
(45) **Date of Patent:** **** Sep. 1, 2015**

- (54) **TIRE**
- (71) Applicant: **The Goodyear Tire & Rubber Company, Akron, OH (US)**
- (72) Inventors: **Vincent Benoit Mathonet, Harze (BE); Philippe Joseph Auguste Muller, Champlon (BE); Albert Maurice Pol Ghislain Lerusse, Bastogne (BE)**
- (73) Assignee: **The Goodyear Tire & Rubber Company, Akron, OH (US)**
- (**) Term: **14 Years**
- (21) Appl. No.: **29/473,936**
- (22) Filed: **Nov. 27, 2013**
- (51) **LOC (10) Cl.** **12-15**
- (52) **U.S. Cl.**
USPC **D12/601**
- (58) **Field of Classification Search**
USPC D12/568-603; 152/209.1-209.28
CPC B60C 11/11; B60C 2011/1213; B60C 11/00;
B60C 11/04; B60C 11/1281; B60C
2011/0374; B60C 1/0016; B60C 11/12;
B60C 11/0306; B60C 11/0309; B60C 11/13;
B60C 11/042
See application file for complete search history.

D583,752 S	*	12/2008	Georges et al.	D12/553
D584,217 S		1/2009	Scheuren et al.	D12/549
D592,589 S		5/2009	Dixon et al.	D12/600
D604,228 S		11/2009	Le et al.	D12/582
D604,229 S		11/2009	Le et al.	D12/582
D604,690 S	*	11/2009	Dixon et al.	D12/579
D605,108 S		12/2009	Brown et al.	D12/588
D609,169 S		2/2010	Feider	D12/588
D613,676 S		4/2010	Nicolas et al.	D12/567
D614,121 S		4/2010	Janesh et al.	D12/597
D620,430 S		7/2010	Gillard et al.	D12/600
D627,710 S		11/2010	Rodicq et al.	D12/583
D631,001 S		1/2011	Hughes et al.	D12/601
D640,185 S		6/2011	Scheuren et al.	D12/588
D640,969 S		7/2011	Scheuren et al.	D12/588
D645,394 S	*	9/2011	De Staercke et al.	D12/583
D645,810 S		9/2011	Le et al.	D12/600
D647,040 S		10/2011	Mathonet et al.	D12/588
D653,199 S		1/2012	Scheuren et al.	D12/588
D661,640 S		6/2012	Krier	D12/588
D667,365 S		9/2012	Dixon et al.	D12/594
D674,739 S		1/2013	Georges et al.	D12/586
D674,740 S		1/2013	Mathonet et al.	D12/588

* cited by examiner

Primary Examiner — George D Kirschbaum
Assistant Examiner — Jennifer Watkins
(74) *Attorney, Agent, or Firm* — Richard B. O'Planick

(57) **CLAIM**
The ornamental design for a tire, as shown and described.

(56) **References Cited**
U.S. PATENT DOCUMENTS

D315,128 S	*	3/1991	Grass et al.	D12/528
D448,707 S		10/2001	Maziarka et al.	D12/147
D481,670 S		11/2003	Harden, Jr. et al.	D12/595
D481,992 S		11/2003	Harden, Jr. et al.	D12/595
D511,741 S		11/2005	Cazin-Bourguignon et al.	D12/601
D517,468 S		3/2006	Le et al.	D12/566
D541,737 S		5/2007	Cazin-Bourguignon et al.	D12/600
D583,309 S		12/2008	Licht et al.	D12/588

DESCRIPTION

FIG. 1 is a perspective view of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;
FIG. 2 is a front elevational view thereof;
FIG. 3 is a right side elevational view thereof; and,
FIG. 4 is an enlarged fragmentary front elevational view thereof.

1 Claim, 4 Drawing Sheets






FIG - 1




FIG - 2



FIG - 3




FIG - 4