



US00D738710S

(12) **United States Design Patent**
Shin

(10) **Patent No.:** **US D738,710 S**

(45) **Date of Patent:** **** Sep. 15, 2015**

(54) **DAMPER PULLEY FOR VEHICLE**

(71) Applicant: **FUKOKU KOREA CO., LTD.**,
Ansan-si, Gyeonggi-do (KR)

(72) Inventor: **Seung-Woo Shin**, Ansan-si (KR)

(73) Assignee: **FUKOKU KOREA CO., LTD.**,
Ansan-Si, Gyeonggi-Do (KR)

(**) Term: **14 Years**

(21) Appl. No.: **29/484,535**

(22) Filed: **Mar. 11, 2014**

(51) **LOC (10) Cl.** **08-05**

(52) **U.S. Cl.**
USPC **D8/360**

(58) **Field of Classification Search**
USPC D8/360, 356, 354, 349; D15/148, 5,
D15/146, 147, 149; D23/269; 474/8, 29, 31,
474/37, 39, 41, 47-57, 69, 113, 135, 166
CPC B66D 1/00; F16H 59/00
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

75,735	A *	3/1868	Collins et al.	474/177
1,627,572	A *	5/1927	Olinger et al.	254/390
2,352,474	A *	6/1944	Firth et al.	474/98
D297,707	S *	9/1988	Kanemitsu	D8/360
4,824,422	A *	4/1989	Jocic	474/170
D308,013	S *	5/1990	Kanemitsu	D8/360
D317,709	S *	6/1991	Kanemitsu	D8/360
D320,927	S *	10/1991	Kanemitsu	D8/360
D347,378	S *	5/1994	Warner	D8/360
5,540,626	A *	7/1996	Asai et al.	474/94

D459,197	S *	6/2002	Hodjat	D8/360
6,575,536	B2 *	6/2003	Chen	301/35.623
D481,615	S *	11/2003	Hodjat et al.	D8/360
6,669,135	B1 *	12/2003	Hartley	242/390.9
D551,943	S *	10/2007	Hodjat et al.	D8/349
D598,480	S *	8/2009	Kanemitsu	D15/148
7,614,611	B1 *	11/2009	Walton et al.	254/393
D621,240	S *	8/2010	Lutter et al.	D8/356
7,874,411	B2 *	1/2011	Roberts et al.	191/12.2 R
D643,702	S *	8/2011	Kanemitsu et al.	D8/360
D645,334	S *	9/2011	Kanemitsu et al.	D8/360
D654,778	S *	2/2012	Hines et al.	D8/356
D679,572	S *	4/2013	Attaway	D8/349
D716,640	S *	11/2014	Martinson	D8/356
2004/0145123	A1 *	7/2004	Hystad	277/608
2004/0178398	A1 *	9/2004	Miller et al.	254/390

* cited by examiner

Primary Examiner — Cynthia Underwood

(74) *Attorney, Agent, or Firm* — Kile Park Reed & Houtteman PLLC

(57) **CLAIM**

I claim, the ornamental design for a damper pulley for vehicle, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a damper pulley for vehicle, showing my new design;
FIG. 2 is a front view thereof;
FIG. 3 is a rear view thereof;
FIG. 4 is a left side view thereof;
FIG. 5 is a right side view thereof;
FIG. 6 is a top view thereof;
FIG. 7 is a bottom view thereof; and,
FIG. 8 is a cross-sectional view thereof taken along line '8-8' in FIG. 2.

1 Claim, 7 Drawing Sheets




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8

