



US00D739280S

(12) **United States Design Patent**
Petrucelli

(10) **Patent No.:** **US D739,280 S**

(45) **Date of Patent:** **** Sep. 22, 2015**

(54) **TEMPERATURE SENSING CLAMP**

(71) Applicant: **Measurement Ltd.**, Grand Cayman, KY
(US)

(72) Inventor: **Steven Petrucelli**, Cranbury, NJ (US)

(73) Assignee: **Parker Hannifin Corporation**,
Cleveland, OH (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/479,640**

(22) Filed: **Jan. 17, 2014**

(51) **LOC (10) Cl.** **10-04**

(52) **U.S. Cl.**
USPC **D10/79; D10/52**

(58) **Field of Classification Search**
USPC D10/52, 60, 78, 79
CPC G01R 1/22-1/44; G01R 15/00-15/26
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,984,798	A *	10/1976	Bussen	336/176
4,316,142	A *	2/1982	Kuramoto	324/127
4,827,272	A *	5/1989	Davis	343/702
D410,396	S *	6/1999	Iwasaki et al.	D10/78
D678,790	S *	3/2013	Worones	D10/79

OTHER PUBLICATIONS

Pipe Clamp Temp Probe, Type K, 20 to 300F, Grainger Approved Vendor, http://www.grainger.com/product/pipe-clamp-temp-probe-5RMF0?s_pp=false, Apr. 28, 2014, pp. 1-4.
Temperature clamp with bluetooth—Google search, <https://www.google.com/search?q=temperature+clamp+with+bluetooth&source=lnms&tbm=isch&sa>, Apr. 23, 2014, pp. 1-2.
Testo 0613 5505 Temperature Clamp, Testers and Tools, <http://www.testersandtools.com/Testo-0613-5505-Temperature-Clamp.php>, Apr. 23, 2014, pp. 1-2.

Pipe-Clamp Thermocouple 3/8" to 1 3/8" for Air Conditioning ATC1, TruTech Tools, Ltd., http://www.trutechtools.com/Pipe-Clamp-Thermocouple-38-to-1-38-for-Air-Conditioning-ATC1_p_2 . . . , Apr. 23, 2014, pp. 1-7.
HHM-EX845 True RMS 1000 Amp Clamp Meter with Bluetooth, Omega User's Guide, 17 pages, 2012.
Agilent U1210 Series Handheld Clamp Meters, Agilent Technologies, 16 pages, 2004.

* cited by examiner

Primary Examiner — Antoine D Davis


(57) **CLAIM**

The ornamental design for a temperature sensing clamp, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a temperature sensing clamp showing my new design in a closed configuration, according to an embodiment of the invention;
FIG. 2 is a left side elevational view of the temperature sensing clamp of FIG. 1;
FIG. 3 is a top view of the temperature sensing clamp of FIG. 1;
FIG. 4 is a right side elevational view of the temperature sensing clamp of FIG. 1;
FIG. 5 is a bottom view of the temperature sensing clamp of FIG. 1;
FIG. 6 is a front elevational view of the temperature sensing clamp of FIG. 1;
FIG. 7 is a rear elevational view of the temperature sensing clamp of FIG. 1;
FIG. 8 is a left side elevational view of the temperature sensing clamp of FIG. 1 shown in an open configuration;
FIG. 9 is a cross-sectional view of the temperature sensing clamp of FIG. 1 taken along line 9-9, as illustrated in FIG. 2; and,
FIG. 10 is a cross-sectional view of the temperature sensing clamp of FIG. 1 taken along line 10-10, as illustrated in FIG. 2.

1 Claim, 6 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10