



US00D739706S

(12) **United States Design Patent**  
**Klaus**

(10) **Patent No.:** **US D739,706 S**

(45) **Date of Patent:** **\*\* Sep. 29, 2015**

(54) **CABLE LOCK**

D535,177 S \* 1/2007 Hsieh ..... D8/333  
D540,149 S \* 4/2007 Tollefson ..... D8/330  
D557,106 S \* 12/2007 Kuwayama ..... D8/333

(71) Applicant: **Briggs & Stratton Corporation,**  
Wauwatosa, WI (US)

\* cited by examiner

(72) Inventor: **David Norbert Klaus,** Whitefish Bay,  
WI (US)

**OTHER PUBLICATIONS**

(73) Assignee: **Briggs & Stratton Corporation,**  
Wauwatosa, WI (US)

NovaVision, Inc., Cable Security Seals—Product Information,  
retrieved from the internet at: [http://www.novavisioninc.com/pages/prd\\_cable\\_seals.html](http://www.novavisioninc.com/pages/prd_cable_seals.html) on Jan. 22, 2015, 6 pages as printed.

(\*\*) Term: **14 Years**

*Primary Examiner* — Prabhakar Deshmukh

(74) *Attorney, Agent, or Firm* — Foley & Lardner LLP

(21) Appl. No.: **29/506,642**

(57) **CLAIM**

I claim the ornamental design for a cable lock, as shown and described.

(22) Filed: **Oct. 17, 2014**

(51) **LOC (10) Cl.** ..... **08-07**

(52) **U.S. Cl.**

USPC ..... **D8/333**

(58) **Field of Classification Search**

USPC ..... D8/330–333, 339–343, 349, 382, 383,  
D8/394, 396; 70/14–16, 19, 57, 57.1, 58,  
70/141, 158, 224, 225, 226, 233, 431, 416,  
70/465; 292/246–256, 299, 307 R;  
24/17 AP, 16 R, 17 B, 19, 629; 248/73,  
248/74.3

CPC ..... E05B 69/003; E05B 71/00; E05B 73/005

See application file for complete search history.

**DESCRIPTION**


FIG. 1 is a front perspective view from above of the cable lock in a locked configuration;  
FIG. 2 is a front view of the cable lock of FIG. 1;  
FIG. 3 is a rear view of the cable lock of FIG. 1;  
FIG. 4 is a left side view of the cable lock of FIG. 1;  
FIG. 5 is a right side view of the cable lock of FIG. 1;  
FIG. 6 is a top view of the cable lock of FIG. 1;  
FIG. 7 is a bottom view of the cable lock of FIG. 1;  
FIG. 8 is a rear perspective view from above of the cable lock of FIG. 1;  
FIG. 9 is a front perspective view from below of the cable lock of FIG. 1;  
FIG. 10 is a front perspective view from above of the cable lock of FIG. 1 in an unlocked configuration;  
FIG. 11 is a front view of the cable lock of FIG. 1 in an unlocked configuration; and,  
FIG. 12 is a top view of the cable lock of FIG. 1 in an unlocked configuration.  
Stipple shading is used to indicate a cable strand of a contrasting color to the unshaded cable strands.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

D228,618 S \* 10/1973 Falk ..... D8/333  
3,844,118 A \* 10/1974 Wilkinson ..... 60/251  
D242,112 S \* 11/1976 Sander ..... D8/333  
5,868,012 A \* 2/1999 Chun-Te et al. .... 70/30  
D436,015 S \* 1/2001 Yu ..... D8/333  
D436,834 S \* 1/2001 Aichmann ..... D8/333  
6,227,016 B1 \* 5/2001 Yu ..... 70/30  
D450,560 S \* 11/2001 Yu ..... D8/333  
6,389,854 B1 \* 5/2002 Huang ..... 70/58

**1 Claim, 7 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3



FIG. 4



FIG. 5



FIG. 6



FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12