US00D742394S

(12) **United States Design Patent**
Bouchard et al.

(10) **Patent No.: US D742,394 S**
(45) **Date of Patent: ** Nov. 3, 2015**

(54) **DISPLAY SCREEN, OR PORTION THEREOF, WITH GRAPHICAL USER INTERFACE FOR AN OPTICAL FIBER MICROSCOPE**

(71) Applicant: **EXFO INC.**, Quebec (CA)

(72) Inventors: **Pascal Bouchard**, Quebec (CA); **Leo Gagne**, Quebec (CA); **Karl Poulin**, Quebec (CA)

(73) Assignee: **EXFO INC.**, Quebec, QC

(**) Term: **14 Years**

(21) Appl. No.: **29/468,236**

(22) Filed: **Sep. 27, 2013**

(51) **LOC (10) Cl.** **14-04**

(52) **U.S. Cl.**
USPC **D14/485**

(58) **Field of Classification Search**
USPC D14/485–488, 489, 492, 494, 495
CPC G06F 3/04842; G06F 3/0482; G06F 3/04817
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,602,997	A *	2/1997	Carpenter et al.	715/764
D441,761	S *	5/2001	Machida et al.	D14/486
D591,306	S *	4/2009	Setiawan et al.	D14/486
D592,219	S *	5/2009	Agarwal et al.	D14/486
D602,036	S *	10/2009	Kasuya et al.	D14/486
D609,716	S *	2/2010	White et al.	D14/486
D629,418	S *	12/2010	Brown et al.	D14/486
D631,888	S *	2/2011	Vance et al.	D14/486
D670,724	S *	11/2012	Mori et al.	D14/486
D681,047	S *	4/2013	Park et al.	D14/486
D682,860	S *	5/2013	Hudson et al.	D14/486
2009/0183076	A1 *	7/2009	Shim et al.	715/716
2011/0052144	A1 *	3/2011	Abbas et al.	386/240
2013/0111405	A1 *	5/2013	Park	715/811
2013/0198669	A1 *	8/2013	Gao et al.	715/771
2015/0106748	A1 *	4/2015	Monte et al.	715/753

OTHER PUBLICATIONS

Exfo Inc., "ConnectorMax Analysis Software—Delivering Fast Pass/Fail Assessment of Connector Endfaces", Specification Sheet, Apr. 2011, pp. 1-6, Canada.

(Continued)

Primary Examiner — Sheryl Lane
Assistant Examiner — Nicole Shiflet
(74) *Attorney, Agent, or Firm* — Norton Rose Fulbright Canada LLP; Alexandre Daoust

(57) **CLAIM**

The ornamental design for a display screen, or portion thereof, with graphical user interface for an optical fiber microscope, as shown and described.

DESCRIPTION

FIG. **1** is a front view of a display screen, or portion thereof, with graphical user interface for an optical fiber microscope, showing our new design;
FIG. **2** is a front view of a second embodiment thereof;
FIG. **3** is a front view of a third embodiment thereof; and,
FIG. **4** is a front view of a fourth embodiment thereof.

The oblique line showing and solid black showing in the figures are used as symbols in accordance with MPEP 608.02 IX to illustrate the green color and the black color, respectively. Different forms of stippled surface shadings are used to represent contrasts. The broken lines showing text, graphical elements, and the display screen are included for the purpose of illustrating environmental subject-matter only, and form no part of the claimed design.

1 Claim, 4 Drawing Sheets



(56) **References Cited**

OTHER PUBLICATIONS

JDSU Uniphase Corporation, "P5000 Digital Probe Microscope and FiberChekPRO—Automated Fiber Inspection and Analysis Software & Probe", Technical Note, Feb. 2012, available at http://www.jdsu.com/ProductLiterature/FiberCheckPro-P5000-ds-fit-tm-ae.pdf.

Optical Design Manufacturing Inc., "ODM VIS Image Manager", Software Manual, Retrieved from Internet on Nov. 1, 2013 at http://www.odm-inc.com/support/downloads/ODM_VIS_Image_Manager_Software_Manual_v1.0.0.pdf.

Lightel, "ConnectorView Plus", User's Manual, Retrieved from Internet on Nov. 1, 2013 at http://lightel.com/products/ConnectorView-Plus-v2.pdf.

* cited by examiner


ConnectorMax2
FIP Controls
Focus
High Magnification
Auto centering
Auto focus
Auto capture
Auto analysis
Test Configuration
IEC SM SF APC
Connector Type
125 um
Single fiber
Power Meter
Insertion Loss
Auto: 1625 nm
Ref: -42.52 nm
236.5 db
Auto: 1300 nm
Ref: -25.40 dBm
0.01 db
Auto: 860 nm
Ref: -52 dBm
25.25 db
λ
dB
Ref
Add
VFL Controls
OFF
Blink
ON
Fiber 17
Capture
Open
Save
Report
New Principal
File
Identification...
Test Configuration...
User Preferences...
FIG. 1


Capture
Open
Save
Report
Menu principal
File
Identification...
Test Configuration...
User Preferences...
High Magnification
Auto centering
Auto focus
Auto capture
Auto analysis
Single fiber
Power Meter
Insertion Loss
Auto: 1625 nm
Ref: -42.52 nm
236.5 db
Auto: 1300 nm
Ref: -20.40 dBm
0.01 db
Auto: 850 nm
Ref: -52 dBm
25.25 db
dB
Ref
Add
VFL Controls
OFF
Blink
ON
Fiber 17

FIG. 2


Capture
Open
Save
Report
Menu principal
File
Identification...
Test Configuration...
User Preferences...
ConnectorMax2
FIP Controls
Focus
High Magnification
Auto centering
Auto capture
Auto analysis
Test Configuration
IEC SM SF APC
Cladding Diameter
Connector Type
125 um
Single fiber
Power Meter
Insertion Loss
Auto: 1625 nm
Ref: -42.52 nm
236.5 db
Auto: 1300 nm
Ref: -25.40 dBm
0.01 db
Auto: 850 nm
Ref: -52 dBm
25.25 db
λ
dB
Ref
Add
VFL Controls
OFF
Blink
ON
Fiber 17


ConnectorMax2
Capture
Open
Save
Report
Identification...
Test Configuration...
User Preferences...
Fiber 17
Power Meter
Insertion Loss
Auto: 1625 nm
Ref: -42.52 nm
236.5 db
Auto: 1300 nm
Ref: -25.40 dBm
0.01 db
Auto: 660 nm
Ref: -52 dBm
25.25 db
dB
Ref
Add
VFL Controls
OFF
Blink
ON
High Magnification
Auto centering
Auto focus
Auto capture
Auto analysis
125 um
Single fiber
Fiber Controls

Fig. 4