



US00D744226S

(12) **United States Design Patent**
Wise et al.

(10) **Patent No.:** **US D744,226 S**
(45) **Date of Patent:** **** Dec. 1, 2015**

(54) **GATHERED BOOT CUFF WITH STRAIGHT INSERT**

3,338,237 A * 8/1967 Sconce 602/13
3,435,544 A * 4/1969 Lish 36/2 R
4,771,553 A * 9/1988 Smithdeal 36/1

(71) Applicant: **12Paws LLC**, Marietta, GA (US)

(Continued)

(72) Inventors: **Leslie J. Wise**, Marietta, GA (US); **Ellen V. Cooper**, Marietta, GA (US)

OTHER PUBLICATIONS

(73) Assignee: **12PAWS LLC**, Marietta, GA (US)

Wise, Leslie J.; U.S. Patent Design Application entitled: Boot Cuff With Tapered Insert, U.S. Appl. No. 29/504,435, filed Oct. 6, 2014, 8 pgs.

(**) Term: **14 Years**

(Continued)

(21) Appl. No.: **29/504,437**

Primary Examiner — Elizabeth J Oswecki

(22) Filed: **Oct. 6, 2014**

(74) *Attorney, Agent, or Firm* — Taylor English Duma LLP

(51) **LOC (10) Cl.** **02-07**

(57) **CLAIM**

(52) **U.S. Cl.**

The ornamental design for a gathered boot cuff with a straight insert, as shown and described.

USPC **D2/976**

DESCRIPTION

(58) **Field of Classification Search**

USPC D2/896, 901, 946, 909-914, 970, 976,
D2/980, 858, 894, 625, 983; 36/83, 55,
36/136, 101, 132, 71.5, 72 R, 1, 1.5, 50.1;
2/59, 60, 61, 62, 70

CPC A43B 23/04; A43B 23/07; A43B 3/0078;
A43B 3/0084; A43B 3/02; A43B 3/24;
A43B 3/242; A43B 3/00; A43B 3/04; A43B
3/06; A43B 3/08; A43B 23/00; A41D 17/00;
A41D 17/005; A41D 17/02; A41D 17/04;
A41D 13/06; A41D 13/065; A41D 13/08;
A41D 13/088; A41D 27/10; A43C 11/02;
A43C 19/00; A41B 7/00; A41B 7/10; A41B
7/12

See application file for complete search history.



FIG. 1 is a perspective view of a gathered boot cuff with straight insert showing our new design; FIG. 2 is a front elevation view thereof; FIG. 3 is a back elevation view thereof; FIG. 4 is a left side elevation view thereof; FIG. 5 is a right side elevation view thereof; FIG. 6 is a top plan view thereof; FIG. 7 is a bottom plan view thereof; FIG. 8 is another front elevation view thereof in an inside-out configuration; FIG. 9 is another front elevation view thereof with the straight insert in an inverted position with the insert pulled upward and out of the boot cuff; FIG. 10 is a front perspective view thereof, shown in a used condition with a boot shown in broken lines; and, FIG. 11 is a rear perspective view thereof, shown in a used condition with a boot shown in broken lines. The broken lines on the gathered boot cuff with a straight insert represent thread stitching. The broken line drawings of a boot shown in FIGS. 10 and 11 show environmental structure and form no part of the claimed design.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,435,047 A * 11/1922 Blum 2/61
D63,596 S * 12/1923 Tweedie D2/901
D120,887 S * 6/1940 Grezlak D2/901
D133,870 S * 9/1942 Hill D2/901
3,083,373 A * 4/1963 Rizzotto 2/270

1 Claim, 7 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D321,582 S * 11/1991 Pennington D2/901
D345,252 S * 3/1994 Randall D2/901
D354,615 S * 1/1995 Parker D2/901
D376,472 S * 12/1996 Hatfield D2/976
D386,297 S * 11/1997 Minnick et al. D2/980
D434,214 S * 11/2000 Burns D2/976
D440,030 S * 4/2001 Revis D2/901
D505,777 S * 6/2005 Dunlap D2/901
D596,390 S * 7/2009 Kennedy D2/976
D598,642 S * 8/2009 Plumert D2/976

D599,981 S * 9/2009 Kim D2/901
D599,982 S * 9/2009 Kim D2/901
D625,085 S * 10/2010 Frase et al. D2/901
D629,596 S * 12/2010 Ng D2/970
D636,154 S * 4/2011 Teichert et al. D2/901
D706,024 S * 6/2014 Ng D2/970
D734,595 S * 7/2015 Brown D2/901

OTHER PUBLICATIONS

Wise, Leslie J.; Notice of Allowance for U.S. Appl. No. 29/504,435,
filed Oct. 6, 2014, mailed Aug. 17, 2015, 15 pgs.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11