



US00D744939S

(12) **United States Design Patent**
Hutz et al.

(10) **Patent No.:** **US D744,939 S**
(45) **Date of Patent:** **** Dec. 8, 2015**

(54) **TIRE TREAD**

(71) Applicants: **Compagnie Generale Des Etablissements Michelin,** Clermont-Ferrand (FR); **Michelin Recherche et Technique S.A.,** Granges-Paccot (CH)
(72) Inventors: **John A. Hutz,** Greer, SC (US); **Lyle James,** Dayton, OH (US); **Scott Norville,** Greer, SC (US); **David Pressley,** Taylors, SC (US); **Ed Ware,** Simpsonville, SC (US); **Brad Weaver,** Greenville, SC (US)
(73) Assignees: **MICHELIN RECHERCHE et TECHNIQUE S.A.,** Granges-Paccot (CH); **COMPAGNIE GENERALE DES ETABLISSEMENTS MICHELIN,** Clermont-Ferrand (FR)

(**) Term: **14 Years**

(21) Appl. No.: **29/485,809**

(22) Filed: **Mar. 24, 2014**

(51) **LOC (10) Cl.** **12-15**

(52) **U.S. Cl.**
USPC **D12/599**

(58) **Field of Classification Search**
USPC D12/568-603; 152/209.1-209.28
CPC B60C 11/0306; B60C 11/04; B60C 11/12; B60C 11/13; B60C 11/11; B60C 11/005; B60C 11/1307; B60C 1/0016; B60C 2011/1213
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D483,718 S	12/2003	Hutz et al.	
D530,265 S	10/2006	Hutz et al.	
D608,272 S *	1/2010	Osaka	D12/579
D627,708 S *	11/2010	Carter	D12/579
D661,639 S *	6/2012	Carter	D12/579
D686,568 S *	7/2013	Audigier	D12/600
D695,210 S	12/2013	Tanaka	
D730,272 S *	5/2015	Fleckner	D12/580

OTHER PUBLICATIONS

XZL, Michelin Tire, www.michelinman.com. at least as early as Dec. 3, 2013, 3 pages.
XTY 2, Michelin Tire, www.michelinman.com. at least as early as Dec. 3, 2013, 3 pages.
XS, Michelin Tire, www.michelinman.com. at least as early as Dec. 3, 2013, 2 pages.

* cited by examiner

Primary Examiner — George D Kirschbaum
Assistant Examiner — Jennifer Watkins
(74) *Attorney, Agent, or Firm* — Dority & Manning, P.A.


(57) **CLAIM**

The ornamental design for a tire tread, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire tread showing our new design, it being understood that the tread pattern repeats circumferentially throughout the outer circumference and shoulder of the tire, the opposite side perspective being identical thereto;
FIG. 2 is a front elevation view thereof; and,
FIG. 3 is a side elevation view of the right side thereof, the left side elevation being identical thereto.
In the drawings, the recessed groove portions of the tire tread having a depth is best illustrated along the top and bottom edges of FIG. 2. In the drawings, the broken line disclosure of the tire sidewall and inner bead depicts environmental structure and forms no part of the claimed design.

1 Claim, 3 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3