US00D745420S

(12) United States Design Patent

Li

(10) **Patent No.: US D745,420 S**

(45) **Date of Patent: ** Dec. 15, 2015**

(54) **TEMPERATURE CONTROLLER**

(71) Applicant: **HaiLin Energy Technology Inc.**, Beijing (CN)

(72) Inventor: **Haiqing Li**, Beijing (CN)

(73) Assignee: **HaiLin Energy Technology Inc.**, Beijing (CN)

(**) Term: **14 Years**

(21) Appl. No.: **29/517,630**

(22) Filed: **Feb. 13, 2015**

(30) **Foreign Application Priority Data**

Jan. 14, 2015 (CN) 2015 3 0010854

(51) **LOC (10) Cl.** **10-04**

(52) **U.S. Cl.**
USPC **D10/50**

(58) **Field of Classification Search**
USPC D10/49–50; D9/414, 432, 433; D13/162, 163; D14/126, 336, 371, D14/374, 389
CPC F23N 5/20; F23N 5/203; F23N 5/206; F23N 5/18; F23N 5/184; F23N 5/187; F23N 5/22; F23N 2025/12; F23N 2041/02; F24F 11/00; F24F 11/0012; F24F 11/0009; F24F 11/001; F24F 2011/0057; F24F 2011/0073; F24F 2011/0091
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D261,234	S	*	10/1981	Abraham	D9/432
D387,982	S	*	12/1997	Kaplan	D9/423
D568,257	S	*	5/2008	Tatsuyama et al.	D13/162
D601,353	S	*	10/2009	Sadler et al.	D6/308
D622,513	S	*	8/2010	Tang et al.	D6/308
D630,169	S	*	1/2011	Nakai et al.	D13/168
7,867,646	B2	*	1/2011	Rhodes	429/100
D640,992	S	*	7/2011	Margolin et al.	D13/162
D648,642	S	*	11/2011	Wallaert et al.	D10/50
D649,073	S	*	11/2011	Baskinger et al.	D10/60
D662,094	S	*	6/2012	Mack et al.	D14/388
D678,218	S	*	3/2013	Sheen	D13/168
D687,388	S	*	8/2013	Baumgartner et al.	D13/162
D690,295	S	*	9/2013	Fletcher et al.	D14/336
D694,718	S	*	12/2013	Baumgartner et al.	D13/168
D695,410	S	*	12/2013	Becker	D24/186
D696,636	S	*	12/2013	Sakai	D13/168
D699,130	S	*	2/2014	Rhodes et al.	D10/50
8,644,009	B2	*	2/2014	Rylski et al.	361/679.01
D705,093	S	*	5/2014	Edgar	D10/50
D711,837	S	*	8/2014	Clymer et al.	D13/162
D719,854	S	*	12/2014	Edgar	D10/50

(Continued)

Primary Examiner — Antoine D Davis

(74) *Attorney, Agent, or Firm* — Wolf, Greenfield & Sacks, P.C.

(57) **CLAIM**

The ornamental design for a temperature controller, as shown and described.

DESCRIPTION

FIG. **1** is a front view of a temperature controller according to the present application;

FIG. **2** is a rear view of the temperature controller according to the present application;

FIG. **3** is a left view of the temperature controller according to the present application;

FIG. **4** is a right view of the temperature controller according to the present application;

FIG. **5** is a top view of the temperature controller according to the present application;

FIG. **6** is a bottom view of the temperature controller according to the present application; and,

FIG. **7** is a perspective view of the temperature controller according to the present application.

The broken lines shown in FIGS. **2-6** represent unclaimed portions of the temperature controller and form no part of the claimed design.

1 Claim, 4 Drawing Sheets





(56) **References Cited**

U.S. PATENT DOCUMENTS

D719,855	S *	12/2014	Edgar	D10/50
8,922,493	B2 *	12/2014	Kim	345/169
D724,035	S *	3/2015	Flowers et al.	D13/162
D727,271	S *	4/2015	Shi et al.	D13/162
D727,857	S *	4/2015	Acera et al.	D13/162

* cited by examiner



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6



Fig. 7