



US00D745743S

(12) **United States Design Patent**
Reukema et al.

(10) **Patent No.:** **US D745,743 S**
(45) **Date of Patent:** **** Dec. 15, 2015**

- (54) **CHILD’S ARTICLE SAFETY TETHER**
- (71) Applicants: **Brian Christopher Reukema**,
Southlake, TX (US); **Melissa Christine Reukema**,
Southlake, TX (US)
- (72) Inventors: **Brian Christopher Reukema**,
Southlake, TX (US); **Melissa Christine Reukema**,
Southlake, TX (US)

D597,788 S *	8/2009	Ellis	D7/396.2
D625,512 S *	10/2010	Blaney	D3/215
D628,703 S *	12/2010	Rodriguez	D24/199
D699,406 S *	2/2014	Stolte	D30/153
D700,971 S *	3/2014	Alvarado	D24/199
D701,966 S *	4/2014	Owada	D24/199
2008/0149672 A1 *	6/2008	Frauhiger	224/148.6
2009/0256038 A1 *	10/2009	Schaefer	248/206.2
2010/0025441 A1 *	2/2010	Blaney	224/148.6

* cited by examiner

- (**) Term: **14 Years**
- (21) Appl. No.: **29/511,614**
- (22) Filed: **Dec. 12, 2014**

Primary Examiner — Randall Gholson
(74) *Attorney, Agent, or Firm* — Jeffrey Roddy

Related U.S. Application Data

- (63) Continuation-in-part of application No. 29/465,861,
filed on Sep. 2, 2013, now Pat. No. Des. 722,726.
- (51) **LOC (10) Cl.** **29-02**
- (52) **U.S. Cl.**
USPC **D29/101.1**
- (58) **Field of Classification Search**
USPC D29/101.1; 248/102–107, 548;
215/397, 11.6; D3/229, 215; 224/148;
D24/199
CPC A45F 2005/008
See application file for complete search history.

(57) **CLAIM**

The ornamental design for a child’s article safety tether, as shown and described.

DESCRIPTION

FIG. 1 is a top plan view of our new design for a child’s article safety tether;
FIG. 2 is a bottom plan view thereof;
FIG. 3 is a bottom perspective view thereof; and,
FIG. 4 is a cross-sectional view thereof taken along lines 4-4 in FIG. 2.


The safety tether is made from an elastomer and deformable. Lines on the body of FIGS. 1-3 indicate contour only and are not intended to show surface ornamentation. The safety tether is a one-piece elastomeric zig-zag shaped body having at one end, a relatively small annulus with a tail extending therefrom, and a larger annulus at the opposite end of the body. The cross-sectional profile of the safety tether as shown in (FIG. 4), is rhombic.

1 Claim, 3 Drawing Sheets

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,613,657 A *	3/1997	Olaiz	248/102
D417,778 S *	12/1999	Karlin, III	D3/229
6,216,319 B1 *	4/2001	Elkins	24/3.2







FIG. 1






FIG.4