



US00D747323S

(12) **United States Design Patent**
Luciew

(10) **Patent No.:** **US D747,323 S**
(45) **Date of Patent:** **** Jan. 12, 2016**

(54) **WRIST SUPPORT DEVICE**

(71) Applicant: **Michele Lynn Luciew**, Johnstown, PA
(US)

(72) Inventor: **Michele Lynn Luciew**, Johnstown, PA
(US)

(**) Term: **14 Years**

(21) Appl. No.: **29/509,290**

(22) Filed: **Nov. 14, 2014**

(51) **LOC (10) Cl.** **06-06**

(52) **U.S. Cl.**
USPC **D14/460**

(58) **Field of Classification Search**
USPC D14/458-461, 447, 451, 457, 251;
D29/120.1; D24/190-192; D6/601
CPC A47C 7/022; A45D 29/00; A45D 29/22;
A47B 21/0371; A47G 2009/1018; A47G 9/10;
Y10S 248/918; G06F 3/0395
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D326,782 S *	6/1992	Scarcella	D6/354
D399,832 S *	10/1998	Barrette	D14/458
D399,833 S *	10/1998	Barrette	D14/458
D401,795 S *	12/1998	Liao	5/653
D421,359 S *	3/2000	Liao	5/653
D430,573 S *	9/2000	Vadot	D14/461
D432,803 S *	10/2000	Jalkanen	D6/354
D446,353 S *	8/2001	Crary	D28/61
6,402,100 B1 *	6/2002	Rice	A47B 21/0371 248/118
D466,518 S *	12/2002	Chou	D14/459
D553,623 S *	10/2007	Cobb	D14/458
D595,526 S *	7/2009	Mills	D6/601
D612,654 S *	3/2010	Eura	D6/601
D642,846 S *	8/2011	Parish	D6/601
D648,586 S *	11/2011	Yu	D6/601
D722,449 S *	2/2015	Krishtul	D6/601
9,009,897 B2 *	4/2015	Davis	A47G 9/10 5/636
D731,208 S *	6/2015	Fux	D6/601

D732,313 S *	6/2015	Fux	D6/601
D734,546 S *	7/2015	Baker	D28/57
2015/0107615 A1 *	4/2015	Houlder	A45D 29/22 132/73
2015/0108292 A1 *	4/2015	Baker	A45D 29/00 248/118

* cited by examiner

Primary Examiner — Deanna L Pratt

(74) *Attorney, Agent, or Firm* — Mitchell Law PLLC;
Matthew W. Mitchell

(57) **CLAIM**

The ornamental design for a wrist support device, as shown.

DESCRIPTION

FIG. 1 is a perspective view of the wrist support device of the present invention;
 FIG. 2 is a perspective view 20-degree counterclockwise rotation from the view of FIG. 1;
 FIG. 3 is a perspective view 35-degree counterclockwise rotation from the view of FIG. 1;
 FIG. 4 is a perspective view 55-degree counterclockwise rotation from the view of FIG. 1;
 FIG. 5 is a perspective view 75-degree counterclockwise rotation from the view of FIG. 1;
 FIG. 6 is a perspective view 90-degree counterclockwise rotation from the view of FIG. 1;
 FIG. 7 is a side view of the wrist support device of FIG. 1;
 FIG. 8 is a side view 15-degree clockwise rotation from the view of FIG. 7;
 FIG. 9 is a side view 30-degree clockwise rotation from the view of FIG. 7;
 FIG. 10 is a side view 45-degree clockwise rotation from the view of FIG. 7;
 FIG. 11 is a side view 55-degree clockwise rotation from the view of FIG. 7;
 FIG. 12 is a side view 75-degree clockwise rotation from the view of FIG. 7;
 FIG. 13 is a side view 90-degree clockwise rotation from the view of FIG. 7; and,
 FIG. 14 is top plan view of the wrist support device of FIG. 1.

1 Claim, 14 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3



FIG. 4




FIG. 5




FIG. 6




FIG. 7



FIG. 8



FIG. 9



FIG. 10




FIG. 11




FIG. 12




FIG. 13



FIG. 14