



US00D750630S

(12) **United States Design Patent**  
**Nishizawa**

(10) **Patent No.:** **US D750,630 S**  
(45) **Date of Patent:** **\*\* Mar. 1, 2016**

(54) **COORDINATE INPUT INSTRUMENT**  
(71) Applicant: **Wacom Co., Ltd.**, Kazo-shi, Saitama (JP)  
(72) Inventor: **Naoya Nishizawa**, Setagaya-ku (JP)  
(73) Assignee: **Wacom Co., Ltd.**, Kazo-shi (JP)  
(\*\*) Term: **14 Years**

D686,618 S \* 7/2013 Wilson et al. .... D14/411  
D688,666 S \* 8/2013 Kowari  
D691,137 S \* 10/2013 Yeon et al. .... D14/411  
D694,237 S \* 11/2013 Momose et al. .... D14/411  
D695,741 S \* 12/2013 Wang ..... D14/411  
D699,723 S \* 2/2014 Nishizawa ..... D14/411  
D704,187 S \* 5/2014 Eastwood ..... D14/411  
D709,886 S \* 7/2014 Lin ..... D14/411  
D715,298 S \* 10/2014 Hong et al. .... D14/411  
D725,114 S \* 3/2015 Roskopp et al. .... D14/411

(21) Appl. No.: **29/503,733**  
(22) Filed: **Sep. 29, 2014**

(30) **Foreign Application Priority Data**  
Mar. 31, 2014 (JP) ..... 2014-006886  
(51) **LOC (10) Cl.** ..... **07-05**  
(52) **U.S. Cl.**  
USPC ..... **D14/411**  
(58) **Field of Classification Search**  
USPC ..... D14/372, 496, 432, 371, 125, 126, 129,  
D14/299, 411; D16/300-342; 351/158, 153,  
351/144; 345/7-9, 905; 455/344; 348/115,  
348/53, 121, 739  
CPC ..... G02B 27/017; G06F 3/016; G06F 3/033;  
G06F 3/0317; G06F 3/03545; G06F 3/041;  
G06K 9/222  
See application file for complete search history.

**FOREIGN PATENT DOCUMENTS**

JP D1384580 S 4/2010

\* cited by examiner

*Primary Examiner* — Austin Murphy  
(74) *Attorney, Agent, or Firm* — Christensen O'Connor Johnson Kindness PLLC


(57) **CLAIM**  
The ornamental design for a coordinate input instrument, as shown and described.


**DESCRIPTION**

FIG. 1 is a perspective view of a coordinate input instrument according to my new design;  
FIG. 2 is a top plan view of the coordinate input instrument of FIG. 1;  
FIG. 3 is a front view of the coordinate input instrument of FIG. 1, the rear view of the coordinate input instrument being mirror symmetrical;  
FIG. 4 is a bottom view of the coordinate input instrument of FIG. 1;  
FIG. 5 is a left side view of the coordinate input instrument of FIG. 1; and,  
FIG. 6 is a right side view of the coordinate input instrument of FIG. 1.  
The broken lines show portions of the coordinate input instrument which form no part of the claimed design.


(56) **References Cited**  
**U.S. PATENT DOCUMENTS**  
D431,598 S \* 10/2000 Kim et al. .... D19/119  
D527,050 S \* 8/2006 Hirota ..... D19/177  
D584,355 S \* 1/2009 Hidaka et al. .... D14/411  
D595,718 S \* 7/2009 Richter et al. .... D14/411  
D614,622 S \* 4/2010 Nakata ..... D14/411  
D617,327 S 6/2010 Crisp  
D617,328 S \* 6/2010 Nakata ..... D14/411  
D675,621 S \* 2/2013 Fletcher et al. .... D14/411  
D682,833 S 5/2013 Paschke

**1 Claim, 3 Drawing Sheets**







**FIG. 1**




**FIG. 2**




**FIG. 3**



**FIG. 4**



**FIG. 6**



**FIG. 5**