



US00D752423S

(12) **United States Design Patent**
Smeja

(10) **Patent No.:** **US D752,423 S**
(45) **Date of Patent:** **** Mar. 29, 2016**

- (54) **SET SCREW**
- (71) Applicant: **Sno-Gem, Inc.**, McHenry, IL (US)
- (72) Inventor: **Michael V. Smeja**, Inverness, IL (US)
- (73) Assignee: **Sno-Gem, Inc.**, McHenry, IL (US)
- (**) Term: **14 Years**
- (21) Appl. No.: **29/473,280**
- (22) Filed: **Nov. 20, 2013**
- (51) **LOC (10) Cl.** **08-08**
- (52) **U.S. Cl.**
USPC **D8/387**
- (58) **Field of Classification Search**
USPC D8/387, 349, 397; D22/115, 116, 199;
411/372.5, 373, 378, 380, 387.1,
411/387.3, 387.8, 393, 402, 403, 429, 919;
285/90
CPC F16B 35/005; F16B 35/00; F16B 23/00;
B21D 1/14; B21D 1/00; B25B 13/06; B25B
13/48; B25B 23/0007; B25B 23/0085; B25B
13/488; F42B 6/00; F42B 6/10; F42B 15/00;
F42B 10/24
See application file for complete search history.

- (56) **References Cited**
U.S. PATENT DOCUMENTS
3,662,804 A * 5/1972 Krywitsky et al. 411/259
D283,301 S * 4/1986 Spitz D8/382
D415,676 S * 10/1999 Negishi et al. D8/387
6,283,973 B1 * 9/2001 Hubbard et al. 606/104

D464,254	S	*	10/2002	Monson	D8/387
D466,001	S	*	11/2002	Monson	D8/387
D469,345	S	*	1/2003	Berry et al.	D8/397
7,135,025	B2	*	11/2006	Pohjonen et al.	606/321
7,320,570	B2	*	1/2008	Czarnek	411/393
D580,261	S	*	11/2008	Bulte	D8/387
D590,704	S	*	4/2009	Brunsteter	D8/387
D628,292	S	*	11/2010	Berberich	D24/145
7,883,308	B2	*	2/2011	Hung	411/393
8,057,144	B2	*	11/2011	Johnson et al.	411/34
8,388,294	B2	*	3/2013	Lanneree	411/403
8,794,891	B1	*	8/2014	Saito	411/393
D726,531	S	*	4/2015	Muzic	D8/387
2005/0180839	A1	*	8/2005	Czarnek	411/393
2006/0182513	A1	*	8/2006	Dortch	411/338
2012/0177461	A1	*	7/2012	Balbo Di Vinadio	411/393
2014/0154029	A1	*	6/2014	Pelc	411/372.5

* cited by examiner

Primary Examiner — Wan Laymon
Assistant Examiner — Mark Booker
(74) *Attorney, Agent, or Firm* — Reed Smith, LLP

(57) **CLAIM**
The ornamental design for a set screw, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of a first embodiment of a set screw in accordance with the present invention; FIG. 2 is a side view of the set screw of FIG. 1; FIG. 3 is a front view of the set screw of FIG. 1; and, FIG. 4 is a rear view of the set screw of FIG. 1. The broken lines shown in the Figures represent portions of the set screw that form no part of the claimed design.

1 Claim, 1 Drawing Sheet




FIG. 1




FIG. 2




FIG. 3




FIG. 4

