

US00D752552S

(12) **United States Design Patent**
D'Ascanio et al.

(10) **Patent No.:** **US D752,552 S**
(45) **Date of Patent:** **** Mar. 29, 2016**

(54) **BOLLARD SPEAKER**

(71) Applicants: **Franco D'Ascanio**, Key Colony Beach,
FL (US); **Sean Patrick Snowden**,
Marathon, FL (US)

(72) Inventors: **Franco D'Ascanio**, Key Colony Beach,
FL (US); **Sean Patrick Snowden**,
Marathon, FL (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/510,187**

(22) Filed: **Nov. 25, 2014**

(51) **LOC (10) Cl.** **14-03**

(52) **U.S. Cl.**
USPC **D14/216**

(58) **Field of Classification Search**
USPC D14/168, 170-172, 188, 194-196, 204,
D14/207, 210-216, 219, 221, 222, 224,
D14/496; 181/143, 144, 147, 148, 150, 153,
181/157, 198, 199; 381/300-303, 306, 332,
381/333, 336, 345, 361-364, 386-388;
D12/317; D25/126
CPC B60R 11/0217; G06F 1/1688; H04M 1/03;
H04M 1/035; H04R 1/02; H04R 1/06; H04R
1/021; H04R 1/025; H04R 1/026; H04R
1/028; H04R 1/105; H04R 1/323; H04R
1/403; H04R 1/2803; H04R 1/2834; H04R
5/02; H04R 7/20; H04R 9/06; H04R 9/025;
H04R 2201/021; H04R 2400/00; H04R
2400/07; H04R 2499/11; H04R 2499/13;
H04R 2499/15; H04S 3/00; H04S 7/30

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D254,565 S *	3/1980	Brown	D14/215
D305,893 S *	2/1990	Maloney	D14/215
D316,452 S *	4/1991	Kira	D26/104
D364,165 S *	11/1995	Esslinger	D14/213
D364,405 S *	11/1995	Goldfarb	D14/207
D368,093 S *	3/1996	Starck	D14/189
D579,002 S *	10/2008	Nakao	D14/214
D596,342 S *	7/2009	Sabernig	D26/105
D663,878 S *	7/2012	Ho	D26/67
D664,277 S *	7/2012	Reo	D26/68
D687,809 S *	8/2013	Bergmann	D14/209.1
D726,156 S *	4/2015	Gillespie-Brown	D14/216

* cited by examiner

Primary Examiner — Keli L Hill

(74) *Attorney, Agent, or Firm* — Stuart M. Goldstein

(57) **CLAIM**

The ornamental design for a bollard speaker, as shown and described.

DESCRIPTION

FIG. 1 is a front isometric view of the bollard speaker of the present invention.

FIG. 2 is a front view of the bollard speaker of the present invention.

FIG. 3 is a rear view of the bollard speaker of the present invention.

FIG. 4 is an elevation view of the bollard speaker of the present invention.



FIG. 5 is the opposite elevation view of the bollard speaker of the present invention.

FIG. 6 is a top view of the bollard speaker of the present invention; and,

FIG. 7 is a bottom view of the bollard speaker of the present invention.

The broken lines shown are included for the purpose of illustrating portions of the bollard speaker that form no part of the claim.

1 Claim, 4 Drawing Sheets






FIG. 1




FIG. 3




FIG. 2




FIG. 5




FIG. 4




FIG. 6




FIG. 7