



US00D763199S

(12) **United States Design Patent**  
**Katagiyama et al.**

(10) **Patent No.:** **US D763,199 S**  
(45) **Date of Patent:** **\*\* Aug. 9, 2016**

(54) **POSITIONING TOOL FOR OPTICAL CONNECTOR**

(71) Applicant: **Japan Aviation Electronics Industry, Limited**, Tokyo (JP)

(72) Inventors: **Naoki Katagiyama**, Tokyo (JP); **Yuichi Koreeda**, Tokyo (JP)

(73) Assignee: **JAPAN AVIATION ELECTRONICS INDUSTRY, LIMITED**, Tokyo (JP)

(\*\*) Term: **15 Years**

(21) Appl. No.: **29/528,178**

(22) Filed: **May 27, 2015**

(30) **Foreign Application Priority Data**

Dec. 10, 2014 (JP) ..... 2014-027523

(51) **LOC (10) Cl.** ..... **13-03**

(52) **U.S. Cl.**  
USPC ..... **D13/156**

(58) **Field of Classification Search**  
USPC ..... D13/120–122, 133, 154, 156, 158, 160, 163, 173, 178, 184, 199; 174/50, 520, 67, 174/92, 93; 361/600; 439/723, 752, 135, 439/149, 367; 385/134, 35  
CPC ..... H01R 13/424; H01R 13/436; H01R 13/4362; H01R 13/5213; H01R 13/6392; G02B 6/3831

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

1,823,229 A \* 9/1931 Balbaud ..... A44B 5/02  
24/108  
D179,082 S \* 10/1956 Hudson ..... D13/152  
3,220,078 A \* 11/1965 Preziosi ..... F16B 21/02  
402/80 P

3,686,616 A \* 8/1972 Bowerman ..... H01R 13/443  
24/511  
D244,027 S \* 4/1977 Mooney ..... D13/156  
D251,491 S \* 4/1979 Snyder, Jr. .... D13/146  
D316,402 S \* 4/1991 Baker ..... D13/156  
5,040,867 A \* 8/1991 de Jong ..... G02B 6/3841  
385/60  
D423,460 S \* 4/2000 Lux, Jr. .... D13/152  
6,247,965 B1 \* 6/2001 Cummings ..... H01R 13/4223  
439/148  
6,872,101 B2 \* 3/2005 Daugherty ..... H01R 4/646  
439/726  
8,287,219 B2 \* 10/2012 Opper ..... H01R 11/12  
411/301  
D672,318 S \* 12/2012 Smith ..... D13/156  
D675,167 S \* 1/2013 Smith ..... D13/156

(Continued)

*Primary Examiner* — Derrick Holland

*Assistant Examiner* — Jennifer O King

(74) *Attorney, Agent, or Firm* — Manabu Kanesaka


(57) **CLAIM**

The ornamental design for a positioning tool for an optical connector, as shown and described.

**DESCRIPTION**

FIG. 1 is a front view of a positioning tool for an optical connector showing our new design;  
FIG. 2 is a rear view thereof;  
FIG. 3 is a right side view thereof;  
FIG. 4 is a left side view thereof;  
FIG. 5 is a top plan view thereof;  
FIG. 6 is a bottom plan view thereof;  
FIG. 7 is a perspective view showing a front, top and right side thereof;  
FIG. 8 is a perspective view showing a rear, bottom and left side thereof;  
FIG. 9 is a perspective view showing a front, right side and bottom thereof; and,  
FIG. 10 is a perspective view showing a rear, left side and top thereof.

**1 Claim, 9 Drawing Sheets**



# US D763,199 S

Page 2

---

(56)

## References Cited

### U.S. PATENT DOCUMENTS

9,075,204 B2 *	7/2015	Nishioka .....	G02B 6/3846	2001/0024907 A1 *	9/2001	Murakami .....	H01R 13/443 439/587
D745,117 S *	12/2015	Ramey .....	D23/262	2005/0220419 A1 *	10/2005	Stevens .....	G02B 6/3851 385/55
D747,634 S *	1/2016	Katagiyama .....	D8/14	2007/0104445 A1 *	5/2007	Larson .....	G02B 6/3801 385/134
2001/0017963 A1 *	8/2001	Shimotsu .....	G02B 6/266 385/78	2012/0282788 A1 *	11/2012	Lin .....	H01R 13/443 439/135

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7






FIG. 8




FIG. 9




FIG. 10