



US00D763336S

(12) **United States Design Patent**
Ries

(10) **Patent No.:** **US D763,336 S**
(45) **Date of Patent:** **** Aug. 9, 2016**

(54) **ROBOTIC ARM COMPONENT**

(71) Applicant: **gomtec GmbH, Seefeld (DE)**

(72) Inventor: **Michael Ries, Olching (DE)**

(73) Assignee: **ABB gomtec GmbH (DE)**

(**) Term: **14 Years**

(21) Appl. No.: **29/516,068**

(22) Filed: **Jan. 29, 2015**

(30) **Foreign Application Priority Data**

Jul. 31, 2014 (DE) 40 2014 202 299

(51) **LOC (10) Cl.** **15-99**

(52) **U.S. Cl.**
USPC **D15/199**

(58) **Field of Classification Search**
USPC D15/199; D21/578
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | | |
|----------------|---------|------------|-------|-------------------------|
| D274,182 S * | 6/1984 | Kato | | D15/122 |
| D285,596 S * | 9/1986 | Gimple | | D23/213 |
| D293,449 S * | 12/1987 | Kaufmann | | D15/122 |
| 4,763,401 A * | 8/1988 | Marinoni | | B23K 11/318 279/119 |
| D343,630 S * | 1/1994 | Tomiyama | | D15/199 |
| D344,280 S * | 2/1994 | Koyama | | D15/199 |
| D423,534 S * | 4/2000 | Raab | | D15/199 |
| D440,241 S * | 4/2001 | Kawahara | | D15/199 |
| D443,287 S * | 6/2001 | Kawahara | | D15/199 |
| D461,484 S * | 8/2002 | Kraft | | D15/199 |
| D613,781 S * | 4/2010 | Liu | | D15/199 |
| D624,104 S * | 9/2010 | Miyake | | 15/99 |
| 8,291,789 B2 * | 10/2012 | Long | | B25J 9/102 74/490.01 |
| 8,386,077 B2 * | 2/2013 | Birkenbach | | A61B 19/2203 700/245 |
| D677,294 S * | 3/2013 | Long | | D15/199 |
| D678,378 S * | 3/2013 | Selic | | D15/199 |
| 8,511,197 B2 * | 8/2013 | Liu | | B25J 9/104 74/490.04 |
| 8,561,496 B2 * | 10/2013 | Pan | | B25J 9/101 74/490.01 |
| 8,567,453 B2 * | 10/2013 | Donnay | | B25J 9/0084 141/38 |

| | | | | |
|-------------------|---------|------------|-------|-------------------------|
| D697,104 S * | 1/2014 | Dye | | D15/199 |
| 8,662,234 B2 * | 3/2014 | Roeder | | B62D 5/0418 180/252 |
| D711,061 S * | 8/2014 | Chen | | D34/29 |
| D713,436 S * | 9/2014 | Liu | | D15/199 |
| D716,357 S * | 10/2014 | Gombert | | D15/199 |
| 8,850,696 B2 * | 10/2014 | Baudisch | | B25J 15/0019 29/718 |
| 8,914,152 B2 * | 12/2014 | Scheurer | | 700/250 |
| 8,960,042 B2 * | 2/2015 | Liu | | B25J 9/102 74/490.03 |
| 8,974,372 B2 * | 3/2015 | Fell | | A61B 19/2203 600/114 |
| 8,978,509 B2 * | 3/2015 | Pan | | B25J 9/101 74/490.05 |
| 9,021,915 B2 * | 5/2015 | Long | | B25J 17/00 74/490.05 |
| 9,095,982 B2 * | 8/2015 | Oka | | B25J 17/0283 |
| 9,102,065 B2 * | 8/2015 | Krumbacher | | B25J 17/02 |
| 9,114,525 B2 * | 8/2015 | Long | | B25J 9/104 |
| 9,132,556 B2 * | 9/2015 | Roberts | | B25J 18/00 |
| 2003/0070468 A1 * | 4/2003 | Butscher | | A61C 7/04 72/295 |
| 2010/0178101 A1 * | 7/2010 | Day | | B25J 9/101 403/112 |

* cited by examiner

Primary Examiner — Patricia Palasik



(57) **CLAIM**

The ornamental design for a robotic arm component, as shown.

DESCRIPTION

FIG. 1 is a front perspective view of the robotic arm component according to the present invention;
FIG. 2 is a rear perspective view of the robotic arm component according to the present invention;
FIG. 3 is a front view of the robotic arm component thereof;
FIG. 4 is a back view of the robotic arm component thereof;
FIG. 5 is a left side view of the robotic arm component thereof;
FIG. 6 is a right side view of the robotic arm component thereof;
FIG. 7 is a top view of the robotic arm component thereof;
and,
FIG. 8 is a bottom view of the robotic arm component thereof.

1 Claim, 8 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8