



US00D764397S

(12) **United States Design Patent**
Dixon et al.

(10) **Patent No.:** **US D764,397 S**

(45) **Date of Patent:** **** Aug. 23, 2016**

(54) **TIRE**

(71) Applicant: **The Goodyear Tire & Rubber Company, Akron, OH (US)**

(72) Inventors: **Max Harold Dixon, Kent, OH (US); Ahmad Shafiq Bani Hani, Stow, OH (US); Stephanie Carol Brown, Akron, OH (US); Michael Gordon Smith, Mogadore, OH (US)**

(73) Assignee: **The Goodyear Tire & Rubber Company, Akron, OH (US)**

(**) Term: **14 Years**

(21) Appl. No.: **29/510,765**

(22) Filed: **Dec. 3, 2014**

(51) **LOC (10) Cl.** **12-15**

(52) **U.S. Cl.**
USPC **D12/601**

(58) **Field of Classification Search**
USPC D12/568–603
CPC B60C 5/00; B60C 11/04; B60C 11/11;
B60C 11/13; B60C 11/12; B60C 2011/1213;
B60C 11/03

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D370,439 S	*	6/1996	Feider	D12/588
D384,608 S		10/1997	Schuster	D12/146
D388,370 S		12/1997	Young et al.	D12/146
D397,647 S		9/1998	Young	D12/146
D448,707 S		10/2001	Maziarka et al.	D12/147
D451,860 S		12/2001	Schuster et al.	D12/147
D554,053 S		10/2007	Feider et al.	D12/588
D555,081 S	*	11/2007	Feider	D12/588
D592,589 S		5/2009	Dixon et al.	D12/600
D597,479 S		8/2009	Scharis	D12/586
D604,226 S		11/2009	Scheuren	D12/553
D604,230 S		11/2009	Brown et al.	D12/588

D605,107 S		12/2009	Ludwig et al.	D12/588
D605,108 S		12/2009	Brown et al.	D12/588
D606,011 S	*	12/2009	Ohara	D12/590
D609,169 S		2/2010	Feider	D12/588
D609,170 S		2/2010	Feider et al.	D12/588
D609,175 S		2/2010	Feider et al.	D12/600
D619,085 S		7/2010	Murphy et al.	D12/591
D619,529 S		7/2010	Georges et al.	D12/590
D619,530 S		7/2010	Murphy et al.	D12/591
D642,511 S		8/2011	Strader et al.	D12/587
D656,088 S		3/2012	Krier et al.	D12/591
D664,913 S		8/2012	Le et al.	D12/521

(Continued)

Primary Examiner — George D Kirschbaum

Assistant Examiner — Jennifer Watkins

(74) *Attorney, Agent, or Firm* — Robert N. Lipsik

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a right side elevational view thereof; the opposite side elevational view being identical thereto;



FIG. 4 is an enlarged fragmentary front elevational view thereof;

FIG. 5 is a perspective view of a second embodiment of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread and that the opposite side view is identical thereto; and,

FIG. 6 is a front elevational view of a second embodiment, it being understood that an enlarged fragmentary view thereof would be substantially identical to that shown in FIG. 4, with the exception of the inclusion of the sidewall in solid lines.

In the drawings, the broken line showing of the sidewall, inner bead and the peripheral boundary between the tire tread and the sidewall in FIGS. 1 through 4 depict portions of a tire that form no part of the claimed design.

1 Claim, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D673,897 S 1/2013 Krier D12/587
D674,740 S 1/2013 Mathonet et al. D12/588
D674,741 S 1/2013 Mathonet et al. D12/588
D675,560 S * 2/2013 Kato D12/590

D719,907 S * 12/2014 Ohara D12/588
D730,273 S * 5/2015 Schimmoeller D12/601
D734,246 S * 7/2015 Parr D12/601
D738,294 S * 9/2015 Koog D12/584
D746,222 S * 12/2015 Hutz D12/588

* cited by examiner




FIG-1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-6