



US00D766486S

(12) **United States Design Patent** (10) **Patent No.:** **US D766,486 S**
Boomgaarden et al. (45) **Date of Patent:** **** Sep. 13, 2016**

(54) **LIGHTING DEVICE HAVING A DOMED REFLECTOR**

(71) Applicant: **Lighting Science Group Corporation**,
Satellite Beach, FL (US)

(72) Inventors: **Mark Penley Boomgaarden**, Satellite
Beach, FL (US); **Ricardo Romeu**,
Melbourne, FL (US); **Eric Holland**,
Sunnyvale, CA (US); **Ryan Kelley**,
Denver, CO (US)

(73) Assignee: **Lighting Science Group Corporation**,
Cocoa Beach, FL (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/493,193**

(22) Filed: **Jun. 6, 2014**

(51) **LOC (10) Cl.** **26-05**

(52) **U.S. Cl.**
USPC **D26/74**

(58) **Field of Classification Search**
USPC D26/74, 72, 75, 76, 77, 78, 85, 88, 89,
D26/118, 138, 141; 362/364, 365, 373, 145,
362/146, 147, 148, 150, 153, 153.1, 294,
362/296.01, 296.07, 296.08
CPC F21V 29/2262; F21V 7/06; F21V 21/044;
F21V 21/047; F21V 29/2212; F21V 29/2225;
F21V 29/2256; F21V 29/225; F21V 29/2268;
F21Y 2111/002; F21S 8/02; F21S 8/026
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- D544,127 S * 6/2007 Posey D26/72
- D562,489 S * 2/2008 Rashidi D26/118
- D562,490 S * 2/2008 Rashidi D26/118
- D622,434 S * 8/2010 Ward F21S 8/026
D26/74
- D665,117 S * 8/2012 Yoshida D26/74

- D668,372 S * 10/2012 Renshaw D26/74
- D681,863 S * 5/2013 Chen D26/74
- D684,289 S * 6/2013 Goelz D26/74
- D698,070 S * 1/2014 Messisaen D26/74
- D701,633 S * 3/2014 Snell D26/74
- D704,371 S * 5/2014 Van De Ven D26/74
- D708,381 S * 7/2014 Rashidi D26/74
- 2013/0120963 A1 * 5/2013 Holland F21V 7/0066
362/84

* cited by examiner

Primary Examiner — Angela J Lee

(74) *Attorney, Agent, or Firm* — Mark Malek; Widerman
Malek, PL

(57) **CLAIM**

The ornamental design for a lighting device having a domed reflector, as shown and described.

DESCRIPTION

FIG. 1 is a top perspective view of a lighting device having a domed reflector according to an embodiment of the present invention.

FIG. 2 is a side elevation view of the lighting device having a domed reflector of FIG. 1.

FIG. 3 is another side elevation view of the lighting device having a domed reflector of FIG. 1.

FIG. 4 is yet another elevation view of the lighting device having a domed reflector of FIG. 1.

FIG. 5 is still another side elevation view of the lighting device having a domed reflector of FIG. 1.


FIG. 6 is a top plan view of the lighting device having a domed reflector of FIG. 1.

FIG. 7 is a bottom plan view of the lighting device having a domed reflector of FIG. 1; and,

FIG. 8 is a top perspective view of the lighting device having a domed reflector of FIG. 1, but shown without the broken line elements for clarity of illustration.

The broken lines depict elements of the lighting device having a domed reflector that do not form a claimed feature of the present invention.

1 Claim, 5 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8