



US00D768217S

(12) **United States Design Patent** (10) **Patent No.:** **US D768,217 S**
Yamamoto et al. (45) **Date of Patent:** **** Oct. 4, 2016**

(54) **CAGE OF THRUST ROLLER BEARING**
 (71) Applicants: **Kazuyuki Yamamoto**, Iwata (JP);
Hisataka Hasegawa, Iwata (JP)
 (72) Inventors: **Kazuyuki Yamamoto**, Iwata (JP);
Hisataka Hasegawa, Iwata (JP)
 (73) Assignee: **NTN CORPORATION**, Osaka-shi (JP)
 (**) Term: **14 Years**
 (21) Appl. No.: **29/520,122**
 (22) Filed: **Mar. 11, 2015**

(30) **Foreign Application Priority Data**
 Sep. 16, 2014 (JP) 2014-020434
 (51) **LOC (10) Cl.** **15-09**
 (52) **U.S. Cl.**
 USPC **D15/143**
 (58) **Field of Classification Search**
 USPC D15/143, 199
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | | | |
|-----------|------|---------|----------------|-------|------------|
| 3,256,585 | A * | 6/1966 | Ripple | | 29/898.067 |
| 3,785,710 | A * | 1/1974 | Alling | | 384/623 |
| 3,913,994 | A * | 10/1975 | Alling et al. | | 384/623 |
| 3,994,546 | A * | 11/1976 | Alling | | 384/623 |
| 4,042,285 | A * | 8/1977 | Dorsch | | 384/621 |
| 4,122,589 | A * | 10/1978 | Grimm et al. | | 29/898.067 |
| 5,255,985 | A * | 10/1993 | Alling | | 384/575 |
| 5,626,426 | A * | 5/1997 | Honda et al. | | 384/568 |
| 6,883,968 | B2 * | 4/2005 | Fugel et al. | | 384/577 |
| 7,114,854 | B2 * | 10/2006 | Hayashi et al. | | 384/623 |
| 7,488,114 | B2 * | 2/2009 | Ince | | 384/572 |

| | | | | | |
|-----------|------|---------|-----------------|-------|---------|
| 7,722,257 | B2 * | 5/2010 | Tabata et al. | | 384/571 |
| 7,896,558 | B2 * | 3/2011 | Obayashi et al. | | 384/623 |
| 8,480,307 | B2 * | 7/2013 | Hofmann et al. | | 384/568 |
| 8,596,873 | B2 * | 12/2013 | Hofmann et al. | | 384/523 |
| 8,876,400 | B2 * | 11/2014 | Kanou et al. | | 384/622 |

* cited by examiner
Primary Examiner — Patricia Palasik
 (74) *Attorney, Agent, or Firm* — W. F. Fasse

(57) **CLAIM**
 The ornamental design for a cage of thrust roller bearing, as shown and described.

DESCRIPTION

FIG. 1 is a front view of a cage of thrust roller bearing showing our new design;
 FIG. 2 is a rear view thereof;
 FIG. 3 is a top plan view thereof;
 FIG. 4 is a bottom plan view thereof;
 FIG. 5 is a right side view thereof;
 FIG. 6 is a left side view thereof;
 FIG. 7 is a perspective view thereof;
 FIG. 8 is an enlarged detail view of a portion thereof as indicated in FIG. 7, showing pocket holes and protrusions thereof; and,
 FIG. 9 is an enlarged detail view of a portion thereof as indicated in FIG. 2, showing pocket holes and protrusions thereof.
 The short-dashed broken lines illustrate portions of the cage of thrust roller bearing that form no part of the claimed design. The dash-dotted broken lines in FIGS. 2 and 9 illustrate the boundary of the claimed design, and themselves form no part of the claimed design. The long-dashed broken lines in FIGS. 2, 7, 8 and 9 merely show the perimeters of the enlarged detail views and form no part of the claimed design.

1 Claim, 5 Drawing Sheets




FIG. 1




FIG. 2




FIG.3




FIG.4




FIG.5




FIG. 6



FIG. 7




FIG. 8

FIG. 8




FIG. 9

