



US00D769951S

(12) **United States Design Patent**
Tokura

(10) **Patent No.:** **US D769,951 S**
(45) **Date of Patent:** **** Oct. 25, 2016**

(54) **REFERENCE PLATE**

(71) Applicant: **KYOSHIN KOGYO CO., LTD.**,
Osaka (JP)

(72) Inventor: **Kenji Tokura**, Osaka (JP)

(73) Assignee: **KYOSHIN KOGYO CO., LTD.**,
Osaka (JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/500,349**

(22) Filed: **Aug. 25, 2014**

(30) **Foreign Application Priority Data**

Feb. 25, 2014 (KR) 30-2014-0009373

(51) **LOC (10) Cl.** **15-09**

(52) **U.S. Cl.**
USPC **D15/138**

(58) **Field of Classification Search**
USPC D13/156, 177; D15/138
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- D258,716 S * 3/1981 Ciener D8/343
- D312,611 S * 12/1990 Watson D13/158
- D376,130 S * 12/1996 Elwell D13/158
- 5,742,113 A * 4/1998 Loucks H02N 2/043
310/328
- 5,750,878 A * 5/1998 Bliss G01B 5/0004
33/502
- 5,753,926 A * 5/1998 Sato G03F 9/7015
250/548
- 6,741,358 B1 * 5/2004 Kamiya G03F 7/70483
356/500
- D517,024 S * 3/2006 Fort D13/169

- D528,513 S * 9/2006 Grendahl D13/156
- 7,197,836 B2 * 4/2007 Kikuti G01B 21/042
33/1 CC
- 8,094,345 B2 * 1/2012 Hashizume H04N 1/401
358/461
- D666,973 S * 9/2012 Junko D13/139.3
- 8,537,429 B2 * 9/2013 Sanada H04N 1/00013
358/461
- 8,561,824 B2 * 10/2013 Nakayama B65D 19/16
220/4.29
- 8,611,772 B2 * 12/2013 Aoki G03B 27/54
399/389
- 8,995,027 B2 * 3/2015 Kanaya 358/448

* cited by examiner

Primary Examiner — Patricia Palasik

(74) *Attorney, Agent, or Firm* — Konomi Takeshita

(57) **CLAIM**


The ornamental design for a reference plate, substantially as shown and described.

DESCRIPTION

FIG. 1 is a front view of a reference plate, showing our new design;
FIG. 2 is a rear view thereof;
FIG. 3 is a top plan view thereof;
FIG. 4 is a bottom plan view thereof;
FIG. 5 is a right side view thereof;
FIG. 6 is a left side view thereof; and,
FIG. 7 is a reference view thereof; as shown along line 7-7 in the cross sectional view of the reference plate of FIG. 1. The broken lines in the drawings depict unclaimed environmental subject matter.

The reference plate of this design is used in a heat exchanger manufacturing apparatus, the reference plate being installed in a heat exchanger manufacturing apparatus such that the reference plate can control a moving distance of a reciprocating plate relative to an end plate of a heat exchanger.

1 Claim, 7 Drawing Sheets






FIG.1




FIG. 2




FIG.3




FIG.4



FIG.5




FIG.6




FIG.7