



US00D772762S

(12) **United States Design Patent** (10) **Patent No.:** **US D772,762 S**
Houle (45) **Date of Patent:** **** Nov. 29, 2016**

(54) **VIBRATION ABSORBER**
(71) Applicant: **PLACEMENTS GASTON HOULE INC., Wickham (CA)**
(72) Inventor: **Gaston Houle, Wickham (CA)**
(73) Assignee: **PLACEMENTS GASTON HOULE INC., Wickham (CA)**

8,567,381 B2 10/2013 Saunders
D692,976 S 11/2013 Sims
8,839,775 B2 9/2014 Wasilewski
8,939,139 B2 1/2015 Sims
2002/0088448 A1 7/2002 Sims
2003/0094168 A1 5/2003 Sims
2003/0121510 A1 7/2003 Mizek
2004/0154601 A1 8/2004 Mizek
2009/0032005 A1 2/2009 Wright

(Continued)

(**) Term: **14 Years**

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **29/517,522**

WO WO0040916 7/2000

(22) Filed: **Feb. 13, 2015**

OTHER PUBLICATIONS

(51) **LOC (10) Cl.** **12-16**

(52) **U.S. Cl.**
USPC **D12/159**

(58) **Field of Classification Search**
USPC D22/107; D21/571-575
CPC F41B 5/1426; F41B 5/1407
See application file for complete search history.

Sims String Decelerator by Archery FS Discount Archery Product, published on the website of FS Discount Archery Product (Tustin, CA, USA) published on Feb. 11, 2015. <http://www.fsdiscounarchery.com/simsstringdecelatornew.aspx>.

Primary Examiner — Michael A Pratt

(74) *Attorney, Agent, or Firm* — Mathieu Audet

(56) **References Cited**

(57) **CLAIM**

U.S. PATENT DOCUMENTS


The ornamental design for a vibration absorber, as shown.

3,059,629 A * 10/1962 Stinson F41B 5/00
124/23.1
5,452,704 A 9/1995 Winebarger
5,595,168 A 1/1997 Martin
5,720,269 A 2/1998 Saunders
6,298,842 B1 10/2001 Sims
D454,382 S 3/2002 Sims
6,634,348 B2 10/2003 Gallops, Jr.
6,684,874 B2 2/2004 Mizek
6,761,158 B2 * 7/2004 Wright F41B 5/1407
124/92
6,910,472 B2 6/2005 Mizek
6,966,314 B2 11/2005 McPherson
7,703,449 B2 4/2010 Wright
D648,410 S 11/2011 Sims
D679,357 S 4/2013 Wright

DESCRIPTION

FIG. 1 is an isometric view of the vibration absorber; FIG. 2 is a rear elevational view of the vibration absorber; FIG. 3 is a front elevational view of the vibration absorber; FIG. 4 is a right elevational view of the vibration absorber; FIG. 5 is a left elevational view of the vibration absorber; FIG. 6 is a bottom plan elevational view of the vibration absorber; and, FIG. 7 is a top plan view of view of the vibration absorber. The broken lines in the drawings illustrate portions of the vibration absorber which form no part of the claimed design.

1 Claim, 3 Drawing Sheets



US D772,762 S

Page 2

(56)

References Cited

U.S. PATENT DOCUMENTS

2010/0319670 A1 12/2010 Sims

2011/0214656 A1 9/2011 Saunders
2013/0174825 A1 7/2013 Bednar
2014/0041645 A1 2/2014 Wasilewski

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 5




FIG. 4




FIG. 6




FIG. 7