



US00D775305S

(12) **United States Design Patent** (10) **Patent No.:** **US D775,305 S**  
**Fiocchi et al.** (45) **Date of Patent:** **\*\* Dec. 27, 2016**

(54) **BULLET**

(71) Applicant: **FIOCCHI MUNIZIONI S.p.A.**, Lecco (IT)

(72) Inventors: **Costantino Fiocchi**, Lecco (IT);  
**Andrea Pomi**, Lierna (IT)

(73) Assignee: **FIOCCHI MUNIZIONI S.P.A.**, Lecco (IT)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/525,424**

(22) Filed: **Apr. 29, 2015**

(30) **Foreign Application Priority Data**

Apr. 9, 2015 (EM) ..... 002678185

(51) **LOC (10) Cl.** ..... **22-03**

(52) **U.S. Cl.**  
USPC ..... **D22/116**

(58) **Field of Classification Search**  
USPC ..... D22/115–116; D21/455, 459, 461, 300

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

D729,896 S \* 5/2015 Martinez ..... D22/115

\* cited by examiner

*Primary Examiner* — Michael A Pratt

(74) *Attorney, Agent, or Firm* — Florek & Endres PLLC

(57) **CLAIM**

We claim the ornamental design for a bullet, as shown and described.

**DESCRIPTION**

FIG. 1 is a perspective view of the bullet having four counter-clockwise slots of the present invention.

FIG. 2 is a front elevation of the bullet having four counter-clockwise slots of FIG. 1.

FIG. 3 is a rear elevation of the bullet having four counter-clockwise slots of FIG. 1.

FIG. 4 is a left side elevation of the bullet having four counter-clockwise slots of FIG. 1.

FIG. 5 is a right side elevation of the bullet having four counter-clockwise slots of FIG. 1.

FIG. 6 is a top plan view of the bullet having four counter-clockwise slots of FIG. 1.

FIG. 7 is a bottom plan view of the bullet having four counter-clockwise slots of FIG. 1.

FIG. 8 is a perspective view of the bullet having four clockwise slots of the present invention.

FIG. 9 is a front elevation of the bullet having four clockwise slots of FIG. 8.

FIG. 10 is a rear elevation of the bullet having four clockwise slots of FIG. 8.

FIG. 11 is a left side elevation of the bullet having four clockwise slots of FIG. 8.

FIG. 12 is a right side elevation of the bullet having four clockwise slots of FIG. 8.

FIG. 13 is a top plan view of the bullet having four clockwise slots of FIG. 8.

FIG. 14 is a bottom plan view of the bullet having four clockwise slots of FIG. 8.

FIG. 15 is a perspective view of the bullet having five counter-clockwise slots of the present invention.

FIG. 16 is a front elevation of the bullet having five counter-clockwise slots of FIG. 15.

FIG. 17 is a rear elevation of the bullet having five counter-clockwise slots of FIG. 15.

FIG. 18 is a left side elevation of the bullet having five counter-clockwise slots of FIG. 15.

FIG. 19 is a right side elevation of the bullet having five counter-clockwise slots of FIG. 15.

FIG. 20 is a top plan view of the bullet having five counter-clockwise slots of FIG. 15.

FIG. 21 is a bottom plan view of the bullet having five counter-clockwise slots of FIG. 15.

FIG. 22 is a perspective view of the bullet having five clockwise slots of the present invention.

(Continued)




FIG. 23 is a front elevation of the bullet having five clockwise slots of FIG. 22.

FIG. 24 is a rear elevation of the bullet having five clockwise slots of FIG. 22.

FIG. 25 is a left side elevation of the bullet having five clockwise slots of FIG. 22.

FIG. 26 is a right side elevation of the bullet having five clockwise slots of FIG. 22.

FIG. 27 is a top plan view of the bullet having five clockwise slots of FIG. 22.

FIG. 28 is a bottom plan view of the bullet having five clockwise slots of FIG. 22.

FIG. 29 is a perspective view of the bullet having three counter-clockwise slots of the present invention.

FIG. 30 is a front elevation of the bullet having three counter-clockwise slots of FIG. 29.

FIG. 31 is a rear elevation of the bullet having three counter-clockwise slots of FIG. 29.

FIG. 32 is a left side elevation of the bullet having three counter-clockwise slots of FIG. 29.

FIG. 33 is a right side elevation of the bullet having three counter-clockwise slots of FIG. 29.

FIG. 34 is a top plan view of the bullet having three counter-clockwise slots of FIG. 29.

FIG. 35 is a bottom plan view of the bullet having three counter-clockwise slots of FIG. 29.

FIG. 36 is a perspective view of the bullet having three clockwise slots of the present invention.

FIG. 37 is a front elevation of the bullet having three clockwise slots of FIG. 36.

FIG. 38 is a rear elevation of the bullet having three clockwise slots of FIG. 36.

FIG. 39 is a left side elevation of the bullet having three clockwise slots of FIG. 36.

FIG. 40 is a right side elevation of the bullet having three clockwise slots of FIG. 36.

FIG. 41 is a top plan view of the bullet having three clockwise slots of FIG. 36; and,

FIG. 42 is a bottom plan view of the bullet having three clockwise slots of FIG. 36.

**1 Claim, 12 Drawing Sheets**




FIG. 1




FIG. 2




FIG. 3




FIG. 6




FIG. 5




FIG. 4




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21






FIG. 22




FIG. 23




FIG. 24




FIG. 27




FIG. 26




FIG. 25




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 34




FIG. 33




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 41




FIG. 40




FIG. 42