



US00D777369S

(12) **United States Design Patent** (10) **Patent No.:** **US D777,369 S**
Kennedy (45) **Date of Patent:** **** Jan. 24, 2017**

(54) **LED LIGHT FIXTURE HAVING A SUPPORT THAT IS NOT IN-LINE WITH THE AXIS OF THE CYLINDER**

(71) Applicant: **Avi Corporation**, Chilliwack (CA)

(72) Inventor: **Matthew Kennedy**, Chilliwack (CA)

(73) Assignee: **Loom Inc.**, Chilliwack, BC (CA)

(**) Term: **15 Years**

(21) Appl. No.: **29/528,918**

(22) Filed: **Jun. 2, 2015**

(51) **LOC (10) Cl.** **29-05**

(52) **U.S. Cl.**
USPC **D26/137**

(58) **Field of Classification Search**
USPC D26/1, 24, 72, 118, 137

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

D163,812 S * 7/1951 Mehr D26/63
D659,281 S * 5/2012 Patkus D26/137
D694,936 S * 12/2013 Fang D26/72

* cited by examiner

Primary Examiner — Brian N Vinson

(74) *Attorney, Agent, or Firm* — Davis & Bujold PLLC;
Michael J. Bujold

(57) **CLAIM**

The ornamental design for an LED light fixture having a support that is not in-line with the axis of the cylinder, as shown and described.

DESCRIPTION

FIG. 1 is a front elevation view of the LED light fixture having a support that is not in-line with the axis of the cylinder

FIG. 2 is a right side elevation view of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 1.

FIG. 3 is a top plan view of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 1.

FIG. 4 is a perspective view of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 1.

FIG. 5 is a front elevation view of a first variant of LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 1, the variant having a support with a bulbous bottom.

FIG. 6 is a right side elevation view of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 5.

FIG. 7 is a top plan view of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 5.

FIG. 8 is a perspective view of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 5.

FIG. 9 is a front elevation view of a second variant of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 1, the variant having a thick walled cylinder.

FIG. 10 is a right side elevation view of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 9.

FIG. 11 is a top plan view of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 9.

FIG. 12 is a perspective view of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 9.

FIG. 13 is a front elevation view of a third variant of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 1, the variant having a thick walled cylinder and a support with a bulbous bottom.

FIG. 14 is a right side elevation view of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 13.

(Continued)




FIG. 15 is a top plan view of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 13.

FIG. 16 is a perspective view of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 13.

FIG. 17 is a front elevation view of a fourth variant of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 1, the variant having a support that is uniform in diameter.

FIG. 18 is a right side elevation view of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 17.

FIG. 19 is a top plan view of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 17.

FIG. 20 is a perspective view of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 17.

FIG. 21 is a front elevation view of a fifth variant of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 1, the variant having a thick walled cylinder and a support that is uniform in diameter.

FIG. 22 is a right side elevation view of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 21.

FIG. 23 is a top plan view of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 21; and,

FIG. 24 is a perspective view of the LED light fixture having a support that is not in-line with the axis of the cylinder of FIG. 21.

1 Claim, 24 Drawing Sheets




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7




Figure 8




Figure 9




Figure 10




Figure 11




Figure 12




Figure 13




Figure 14




Figure 15




Figure 16




Figure 17




Figure 18




Figure 19




Figure 20




Figure 21




Figure 22




Figure 23




Figure 24