



US00D777567S

(12) **United States Design Patent**
Diener

(10) **Patent No.:** **US D777,567 S**

(45) **Date of Patent:** **** Jan. 31, 2017**

- (54) **CORD CLAMPING DEVICE**
- (71) Applicant: **FILTROS Y MALLAS INDUSTRIALES, S.A. DE C.V.**,
Guadalupe, Neuvo León (MX)
- (72) Inventor: **Gerardo Strobl Diener**, Guadalupe (MX)
- (73) Assignee: **FILTROS Y MALLAS INDUSTRIALES, S.A. DE C.V.**,
Guadalupe (MX)
- (**) Term: **15 Years**
- (21) Appl. No.: **29/527,484**
- (22) Filed: **May 19, 2015**
- (30) **Foreign Application Priority Data**
Apr. 7, 2015 (MX) MX/f/2015/001164
- (51) **LOC (10) Cl.** **08-08**
- (52) **U.S. Cl.**
USPC **D8/394; D8/356**
- (58) **Field of Classification Search**
USPC D8/394, 395, 396, 382, 72, 354, 356,
D8/355, 73, 371, 373; 248/68.1, 74.3, 62;
285/420
CPC F16L 23/08; F16L 3/085; F16L 3/221;
F16L 3/137; F16L 3/08; E21F
17/02; Y10S 248/913; A44B 21/00
See application file for complete search history.
- (56) **References Cited**
U.S. PATENT DOCUMENTS
534,565 A 2/1895 Magee
2,818,622 A * 1/1958 Clevett, Jr. B65D 63/14
24/115 R

- 4,477,947 A * 10/1984 Lyons F16G 11/00
24/115 F
- 4,909,298 A * 3/1990 Langhart A47H 11/02
160/178.1 R
- D310,166 S * 8/1990 Fildan D8/356
- 5,440,788 A 8/1995 Boden
- D369,960 S * 5/1996 Rohaly D8/396
- D371,172 S * 6/1996 Foreshow 472/71
- D380,375 S * 7/1997 Rohaly D8/394
- D383,053 S * 9/1997 Schrader D23/262
- D388,378 S * 12/1997 Ratliff, Jr. D12/565
- 5,697,128 A 12/1997 Peregrine
- 5,766,700 A 6/1998 Borchers
- D398,227 S * 9/1998 Orkisz D9/423
- 5,970,566 A 10/1999 Girardot et al.
- 6,443,527 B1 9/2002 Borchers et al.
- 6,871,375 B2 3/2005 Borchers
- D517,904 S * 3/2006 Alkalay D8/382
- D520,351 S * 5/2006 Alkalay D8/382

(Continued)

Primary Examiner — Ralf Seifert

(74) *Attorney, Agent, or Firm* — Avery N. Goldstein;
Blue Filament Law PLLC


(57) **CLAIM**

The ornamental design for a cord clamping device, as shown and described.

DESCRIPTION

FIG. 1 shows a bottom perspective view of the device.
 FIG. 2 shows a top perspective view of the device.
 FIG. 3 shows a bottom view of the device.
 FIG. 4 shows a top view of the device.
 FIG. 5 shows a mid-section view in perspective of the device along the line and in the direction of the rays extending therefrom in FIG. 1; and,
 FIG. 6 shows a mid-section view of the device along the line and in the direction of the rays extending therefrom in FIG. 1.

1 Claim, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D610,900	S	*	3/2010	Piermayr	D8/394
7,891,058	B2		2/2011	Kubli		
D664,832	S	*	8/2012	van der Vorst	D8/356
D695,601	S	*	12/2013	Cabrele	D8/396
D698,226	S	*	1/2014	Chance	D13/156
D740,106	S	*	10/2015	Cooper	D8/356
2003/0005557	A1		1/2003	Renn		
2014/0283339	A1		9/2014	Gallagher et al.		

* cited by examiner




FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6