



US00D780882S

(12) **United States Design Patent**  
**Barker**

(10) **Patent No.:** **US D780,882 S**

(45) **Date of Patent:** **\*\* Mar. 7, 2017**

(54) **TIRE PUNCTURING DEVICE**  
(71) Applicant: **Robert Rea Barker**, Huntsville, AL  
(US)  
(72) Inventor: **Robert Rea Barker**, Huntsville, AL  
(US)

D415,974 S \* 11/1999 Arellano ..... D10/113.1  
D462,257 S \* 9/2002 Alexander ..... D8/391  
D493,205 S \* 7/2004 Combes ..... D21/840  
D588,446 S \* 3/2009 Hashim ..... D8/391  
D629,293 S \* 12/2010 DuFour ..... D8/388  
D679,540 S \* 4/2013 Eaton ..... D7/213  
D700,260 S \* 2/2014 Geiger ..... D21/718

(Continued)

(\*\*) Term: **15 Years**

*Primary Examiner* — Manpreet Matharu

*Assistant Examiner* — Suzanne Tisdell

(21) Appl. No.: **29/530,504**

(57) **CLAIM**

(22) Filed: **Jun. 17, 2015**

The ornamental design for a tire puncturing device, as shown and described.

(51) **LOC (10) Cl.** ..... **22-99**

(52) **U.S. Cl.**  
USPC ..... **D22/199**

**DESCRIPTION**

(58) **Field of Classification Search**  
USPC ..... D8/388, 391; D21/312, 333, 387, 686,  
D21/718, 760, 761, 840; D22/117, 199;  
D24/146; D29/124, 130  
CPC E01F 13/12; E01F 9/654; E01F 9/688; F41H  
11/08  
See application file for complete search history.


FIG. 1 is a perspective view of a tire puncturing device;  
FIG. 2 is a front elevational view thereof, the rear elevational view being a mirror image;  
FIG. 3 is a right-side elevational view thereof, the left-side elevational view being a mirror image;  
FIG. 4 is a top plan view thereof;  
FIG. 5 is a bottom plan view thereof;  
FIG. 6 is a bottom perspective view of the ring platform, showing the concave structure underneath;  
FIG. 7 is a bottom perspective view of the hollowed spike, showing that it is hollow down through the base;  
FIG. 8 is a side elevational view of a weapon platform and weapon deployed in the upright position; and,  
FIG. 9 is a side elevational view of a weapon platform and weapon deployed in the side position, showing that the base is loose to allow for an angle of about 30 degrees.  
The broken line showing of a picture in FIG. 8 and FIG. 9 is included for the purpose of showing environmental structure and forms no part of the claimed design.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,346,713 A \* 4/1944 Brooks ..... E01F 13/12  
102/401  
2,912,229 A \* 11/1959 Persgard ..... E01F 13/12  
152/208  
D298,736 S \* 11/1988 Shiraishi ..... D8/382  
4,889,067 A \* 12/1989 Provence, Jr. .... E01F 9/654  
116/63 C  
D313,471 S \* 1/1991 Bremer ..... D24/147  
D322,556 S \* 12/1991 Jeter ..... D8/382  
5,921,703 A \* 7/1999 Becker ..... E01F 13/12  
256/1

**1 Claim, 9 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

D710,682 S *	8/2014	Rose .....	D8/388
D719,798 S *	12/2014	Thompson .....	D8/1
D740,420 S *	10/2015	Spycher .....	D24/146
D748,508 S *	2/2016	Park .....	D10/65
2004/0085194 A1 *	5/2004	Cleland .....	E01F 9/688
			340/332
2009/0263190 A1 *	10/2009	Segal .....	E01F 13/12
			404/6

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6






FIG. 7




FIG. 8




FIG. 9