



US00D782970S

(12) **United States Design Patent**  
**Sato**

(10) **Patent No.:** **US D782,970 S**  
(45) **Date of Patent:** **\*\* Apr. 4, 2017**

(54) **TIRE**  
(71) Applicant: **TOYO TIRE & RUBBER CO., LTD.**,  
Osaka-shi, Osaka (JP)  
(72) Inventor: **Yoshiki Sato**, Osaka (JP)  
(73) Assignee: **TOYO TIRE & RUBBER CO., LTD.**,  
Osaka (JP)  
(\*\*) Term: **14 Years**  
(21) Appl. No.: **29/523,187**  
(22) Filed: **Apr. 7, 2015**  
(30) **Foreign Application Priority Data**  
Jan. 7, 2015 (JP) ..... 2015-000171  
(51) **LOC (10) Cl.** ..... **12-15**  
(52) **U.S. Cl.**  
USPC ..... **D12/605**  
(58) **Field of Classification Search**  
USPC ..... D12/500, 501, 503, 506, 544, 570, 579,  
D12/580, 587, 588, 599, 600, 605; 152/5,  
152/17, 75, 209.1, 246, 324, 326;  
156/113; 180/54.1  
CPC ..... B60C 13/00  
See application file for complete search history.

(56) **References Cited**  
**U.S. PATENT DOCUMENTS**  
D62,423 S \* 5/1923 Simmons ..... D12/503  
D62,856 S \* 8/1923 Simmons ..... D12/503  
D63,665 S \* 12/1923 Smith ..... D12/503  
D67,852 S \* 7/1925 Reichard ..... D12/503  
1,584,785 A \* 5/1926 McCollough ..... B60C 7/12  
152/326  
D100,948 S \* 8/1936 Hower ..... D12/605  
D102,911 S \* 1/1937 Martin ..... D12/605

2,620,844 A \* 12/1952 Lord ..... B60C 7/12  
152/326  
D546,273 S \* 7/2007 Dumigan ..... D12/605  
D629,351 S \* 12/2010 Jacobs ..... D12/600  
(Continued)

**OTHER PUBLICATIONS**

Off-Road.com. First Look: Nitto Ridge Grappler Off-Road Tire; published by Josh Burns. Jun. 1, 2016 [earliest online date], [site visited Jun. 14, 2016]. Available from Internet, <URL:http://www.off-road.com/trucks-4x4/tech/first-look-nitto-ridge-grappler-of-froad-tire-54458.html>.\*



*Primary Examiner* — Robert M Spear  
*Assistant Examiner* — Darcey E Heflin  
(74) *Attorney, Agent, or Firm* — Sterne, Kessler,  
Goldstein & Fox P.L.L.C.

(57) **CLAIM**  
The ornamental design for a tire, as shown and described.

**DESCRIPTION**

FIG. 1 is a perspective view of a tire showing my new design;  
FIG. 2 is a front view thereof;  
FIG. 3 is a rear view thereof;  
FIG. 4 is a top plan view thereof;  
FIG. 5 is a bottom plan view thereof;  
FIG. 6 is a right side view thereof;  
FIG. 7 is a left side view thereof;  
FIG. 8 is an enlarged view taken along lines 8-8 and 8'-8' in FIG. 2; and,  
FIG. 9 is an enlarged cross-sectional view taken along line 9-9 in in FIG. 8.  
In the drawings, the broken lines showing portions of the tire tread, sidewall and inner bead depict portions of the tire that form no part of the claimed design. In FIGS. 1, 2 and 8, the outermost broken line of the sidewall forms the boundary of the claim.

**1 Claim, 9 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

D638,354 S	5/2011	Strader et al.	
D663,259 S	7/2012	Umstot et al.	
D701,825 S	4/2014	Larregain et al.	
D753,055 S *	4/2016	Sato .....	D12/594

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6






FIG. 7




FIG. 8




FIG. 9