



US00D784881S

(12) **United States Design Patent**
Orlando

(10) **Patent No.:** **US D784,881 S**
(45) **Date of Patent:** **** Apr. 25, 2017**

- (54) **BUSHING KIT FOR ALIGNING AN INDEPENDENT REAR SUSPENSION SUB-FRAME TO A VEHICLE BODY**
- (71) Applicant: **Steeda Autosports, Inc.**, Pompano Beach, FL (US)
- (72) Inventor: **Dario Orlando**, Pompano Beach, FL (US)
- (73) Assignee: **Steeda Autosports, Inc.**, Pompano Beach, FL (US)
- (**) Term: **15 Years**
- (21) Appl. No.: **29/544,578**
- (22) Filed: **Nov. 4, 2015**
- (51) **LOC (10) Cl.** **12-16**
- (52) **U.S. Cl.**
USPC **D12/194**
- (58) **Field of Classification Search**
USPC D12/159, 174-175
(Continued)

- (56) **References Cited**
U.S. PATENT DOCUMENTS
D214,338 S * 6/1969 Stone D15/143
D341,145 S * 11/1993 Esworthy D15/143
(Continued)

Primary Examiner — Michael A Pratt
(74) *Attorney, Agent, or Firm* — McHale & Slavin, P.A.

(57) **CLAIM**
The ornamental design for a bushing kit for aligning an independent rear suspension sub-frame to a vehicle body, as shown and described.

DESCRIPTION

FIG. 1 is a top left perspective partial view illustrating a first portion of the bushing kit for aligning an independent rear suspension sub-frame to a vehicle body of the present invention;

FIG. 2 is a top view of the first portion illustrated in FIG. 1;
 FIG. 3 is a bottom view of the first portion illustrated in FIG. 1;
 FIG. 4 is a rear view of the first portion illustrated in FIG. 1;
 FIG. 5 is a front view of the first portion illustrated in FIG. 1;
 FIG. 6 is a right side view of the first portion illustrated in FIG. 1;
 FIG. 7 is a left side view of the first portion illustrated in FIG. 1;
 FIG. 8 is a top front perspective view illustrating a second portion of the bushing kit for aligning an independent rear suspension sub-frame to a vehicle body of the present invention;
 FIG. 9 is a top view of the second portion illustrated in FIG. 8;
 FIG. 10 is a bottom view of the second portion illustrated in FIG. 8;
 FIG. 11 is a rear view of the second portion illustrated in FIG. 8;
 FIG. 12 is a front view of the second portion illustrated in FIG. 8;
 FIG. 13 is a right side view of the second portion illustrated in FIG. 8;
 FIG. 14 is a left side view of the second portion illustrated in FIG. 8;
 FIG. 15 is a perspective view illustrating a third portion of the bushing kit for aligning an independent rear suspension sub-frame to a vehicle body of the present invention;
 FIG. 16 is a top view of the third portion illustrated in FIG. 15;
 FIG. 17 is a bottom view of the third portion illustrated in FIG. 15;
 FIG. 18 is a rear view of the third portion illustrated in FIG. 15;
 FIG. 19 is a front view of the third portion illustrated in FIG. 15;

(Continued)




FIG. 20 is a right side view of the third portion illustrated in FIG. 15;
 FIG. 21 is a left side view of the third portion illustrated in FIG. 15;
 FIG. 22 is a perspective view illustrating a fourth portion of the bushing kit for aligning an independent rear suspension sub-frame to a vehicle body of the present invention;
 FIG. 23 is a top view of the fourth portion illustrated in FIG. 22;
 FIG. 24 is a bottom view of the fourth portion illustrated in FIG. 22;
 FIG. 25 is a rear view of the fourth portion illustrated in FIG. 22;
 FIG. 26 is a front view of the fourth portion illustrated in FIG. 22;
 FIG. 27 is a right side view of the fourth portion illustrated in FIG. 22;
 FIG. 28 is a left side view of the fourth portion illustrated in FIG. 22;
 FIG. 29 is a perspective view illustrating a fifth portion of the bushing kit for aligning an independent rear suspension sub-frame to a vehicle body of the present invention;
 FIG. 30 is a top view of the fifth portion illustrated in FIG. 29;
 FIG. 31 is a side view of the fifth portion illustrated in FIG. 29; and,
 FIG. 32 is an environmental perspective view illustrating the portions of the bushing kit for aligning an independent rear suspension sub-frame to a vehicle body installed onto the rear suspension sub-frame.

The portions of the bushing kit for aligning an independent rear suspension sub-frame to a vehicle body illustrated in broken lines form no part of the claimed subject matter.

1 Claim, 12 Drawing Sheets

(58) **Field of Classification Search**

CPC B60G 11/22; B60G 2204/125; B60G 2202/143; B60G 2202/142; B60G 2204/41; B60G 2202/14; B60G 2206/73; B60W 10/20; B60W 2540/18; B62D 1/046; B62D 1/185; B62D 1/195; B62D 1/187

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,275,429	A *	1/1994	Bunker	B60G 7/02 280/124.177
5,503,374	A *	4/1996	Hellon	B60G 7/02 267/281
5,833,026	A *	11/1998	Zetterstrom	B60G 3/202 180/360
6,752,403	B2 *	6/2004	Allen	B60G 17/005 180/89.12
7,819,411	B2 *	10/2010	Eshelman	B60G 3/20 280/124.135
D630,191	S *	1/2011	Chang	D14/225
7,959,170	B2 *	6/2011	Mauz	B60G 3/20 280/124.109
2010/0276901	A1 *	11/2010	Richardson	B60G 3/20 280/93.512

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30



FIG. 31




FIG. 32