US00D790685S

(12) United States Design Patent

Silkaitis et al.

(10) Patent No.: US D790,685 S
(45) Date of Patent: ** Jun. 27, 2017

(54) **BREATH CAPTURE AND SAMPLE DEVICE**

(71) Applicants: **Danius Silkaitis**, Seattle, WA (US); **Janis P. Skujins**, Minneapolis, MN (US); **Micah T. Somers**, Minneapolis, MN (US); **Caleb O. Vainikka**, Corcoran, MN (US); **Brett R. Johnson**, Roseville, MN (US)

(72) Inventors: **Danius Silkaitis**, Seattle, WA (US); **Janis P. Skujins**, Minneapolis, MN (US); **Micah T. Somers**, Minneapolis, MN (US); **Caleb O. Vainikka**, Corcoran, MN (US); **Brett R. Johnson**, Roseville, MN (US)

(73) Assignee: **GM NAMEPLATE, INC.**, Seattle, WA (US)

(**) Term: **15 Years**

(21) Appl. No.: **29/550,473**

(22) Filed: **Jan. 4, 2016**

(51) **LOC (10) Cl.** **29-02**

(52) **U.S. Cl.**
USPC **D24/110.5**

(58) **Field of Classification Search**
USPC D24/110.5, 164
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

D548,332 S * 8/2007 Hitchcock D24/110.1
D765,831 S * 9/2016 Li D24/110

* cited by examiner

Primary Examiner — Antoine D Davis
(74) *Attorney, Agent, or Firm* — Christensen O'Connor Johnson; Matthew Balint; John Denkenberger

(57) **CLAIM**

The ornamental design for a breath capture and sample device, as shown and described.

DESCRIPTION

FIG. **1** shows a front top isometric view of a breath capture and sample device according to a first embodiment of our new design;
FIG. **2** is a bottom rear isometric view of the breath capture and sample device shown in FIG. **1**;
FIG. **3** shows a front view of the breath capture and sample device shown in FIG. **1**;
FIG. **4** shows a rear view of the breath capture and sample device shown in FIG. **1**;
FIG. **5** shows a top view of the breath capture and sample device shown in FIG. **1**;
FIG. **6** shows a bottom view of the breath capture and sample device shown in FIG. **1**;
FIG. **7** shows a right side view of the breath capture and sample device shown in FIG. **1**;
FIG. **8** shows a left side view of the breath capture and sample device shown in FIG. **1**;
FIG. **9** shows a front top isometric view of a breath capture and sample device according to a second embodiment of our new design;
FIG. **10** is a bottom rear isometric view of the breath capture and sample device shown in FIG. **9**;
FIG. **11** shows a front view of the breath capture and sample device shown in FIG. **9**;
FIG. **12** shows a rear view of the breath capture and sample device shown in FIG. **9**;
FIG. **13** shows a top view of the breath capture and sample device shown in FIG. **9**;
FIG. **14** shows a bottom view of the breath capture and sample device shown in FIG. **9**;
FIG. **15** shows a right side view of the breath capture and sample device shown in FIG. **9**; and,
FIG. **16** shows a left side view of the breath capture and sample device shown in FIG. **9**.
The subject matter shown in phantom lines is hereby disclaimed and forms no part of the claimed invention.

1 Claim, 14 Drawing Sheets





(58) **Field of Classification Search**
CPC A61B 5/0836; A61B 5/097; A61B 5/682; A61M 16/00
See application file for complete search history.



Fig. 1.

Fig. 2.





Fig. 3.



Fig. 4.



Fig. 5.



Fig. 6.



Fig. 8.



Fig. 7.



Fig.9.



Fig. 10.


CONNECTED
CALIBRATE HI
ERROR
LED
USER 1 2 3
CALIBRATE LO
BATTERY

Fig. 11.



Fig. 12.



Fig. 13.



Fig. 14.



Fig. 14.



Fig. 15.