



US00D791063S

(12) **United States Design Patent** (10) **Patent No.:** **US D791,063 S**  
**Simon et al.** (45) **Date of Patent:** **\*\* Jul. 4, 2017**

(54) **TIRE**

(71) Applicant: **The Goodyear Tire & Rubber Company, Akron, OH (US)**

(72) Inventors: **Audrey Marie Paule Simon, Arlon (BE); Stephane Jose Geelen, Attert (LU); Guillaume Francois Marie Torres, Colmar-Berg (LU); Sebastien Willy Fontaine, Vichten (LU); Armand Rene Gabriel Leconte, Bigonville (LU); Sylvain Fourme, Holzem (LU); Stephane Laurent Claude Bokken, Vielsalm (BE)**

(73) Assignee: **The Goodyear Tire & Rubber Company, Akron, OH (US)**

(\*\*) Term: **15 Years**

(21) Appl. No.: **29/547,366**

(22) Filed: **Dec. 3, 2015**

(51) **LOC (10) Cl.** ..... **12-15**

(52) **U.S. Cl.**  
USPC ..... **D12/517**

(58) **Field of Classification Search**  
USPC ..... 152/5, 151, 152.1, 167, 208, 152/209.1-209.28, 246, 450, 526, 527, 152/532, 535, 538, 541; D12/145, D12/500-605, 900-901; D21/425-435, D21/495  
CPC ..... B60C 11/00; B60C 2011/0337; B60C 2011/0339; B60C 2011/0386; B60C 3/00; B60C 3/08; B60C 1/00; B60C 2200/00; B60C 2200/02; B60C 2200/04; B60C 2200/06; B60C 2200/065; B60C 2200/08; B60C 2200/10; B60C 2200/12; B60C 2200/14; B60C 7/00; B60C 7/02; B60C 7/04; B60C 7/06; B60C 7/08; B60C 5/00; B60C 13/00

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D368,684 S *	4/1996	Scarpitti .....	D12/517
D490,045 S	5/2004	Delu et al. ....	D12/519
D559,767 S	1/2008	Graas et al. ....	D12/521
D578,955 S	10/2008	Fontaine et al. ....	D12/524
D586,725 S	2/2009	Fontaine et al. ....	D12/519
D597,474 S *	8/2009	Yamakawa .....	D12/519
D599,276 S	9/2009	Fontaine et al. ....	D12/519
D601,939 S	10/2009	Fontaine et al. ....	D12/519
D606,002 S *	12/2009	Yamakawa .....	D12/519
D607,809 S	1/2010	Fontaine et al. ....	D12/523

(Continued)

*Primary Examiner* — Manpreet Matharu

*Assistant Examiner* — Keith Wilson

(74) *Attorney, Agent, or Firm* — Robert N. Lipsik

(57) **CLAIM**

The ornamental design for a tire, as shown and described.



**DESCRIPTION**

FIG. 1 is a perspective view of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread; FIG. 2 is a front elevational view thereof; FIG. 3 is a right side elevational view thereof; FIG. 4 is a left side elevational view thereof; and, FIG. 5 is an enlarged fragmentary front elevational view thereof.

In the drawings, the broken lines showing of the sidewall, inner bead and the peripheral boundary between the tire tread and the sidewall in FIGS. 1 through 5 depict environmental subject matter and form no part of the claimed design.

The dark stippled surface shading represents the recessed portion of the tread grooves having a depth as best shown in FIG. 2.

**1 Claim, 5 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

D623,586	S	9/2010	Fontaine et al. ....	D12/519
D624,006	S *	9/2010	Lee .....	D12/518
D639,722	S	6/2011	Sieber et al. ....	D12/532
D644,593	S	9/2011	Fontaine et al. ....	D12/523
D654,425	S *	2/2012	Nomura .....	D12/517
D665,335	S *	8/2012	Baumard .....	D12/517
D666,137	S	8/2012	Sieber et al. ....	D12/517
D675,148	S	1/2013	Kiwaki .....	D12/517
D689,430	S	9/2013	Fontaine et al. ....	D12/523
D692,371	S *	10/2013	Fontaine .....	D12/517
D708,116	S	7/2014	Caron et al. ....	D12/523
D710,290	S *	8/2014	Leconte .....	D12/517
D713,778	S	9/2014	Muthigi et al. ....	D12/521
D730,269	S *	5/2015	Maxwell .....	D12/523
D737,751	S *	9/2015	Bourel .....	D12/521
2016/0152087	A1 *	6/2016	Hayashi .....	B60C 11/1392 152/209.18
2016/0152090	A1 *	6/2016	Takemoto .....	B60C 11/0306 152/209.24
2016/0193884	A1 *	7/2016	Takemoto .....	B60C 11/1281 152/209.18

\* cited by examiner






FIG-1




FIG-2






FIG-3




FIG-4




FIG-5