



US00D791694S

(12) **United States Design Patent** (10) **Patent No.:** **US D791,694 S**
Sato (45) **Date of Patent:** **** Jul. 11, 2017**

(54) **TIRE**

(71) Applicant: **Toyo Tire & Rubber Co., Ltd.**,
Osaka-shi, Osaka (JP)

(72) Inventor: **Yoshiki Sato**, Osaka (JP)

(73) Assignee: **Toyo Tire & Rubber Co., Ltd.**, Osaka
(JP)

(**) Term: **15 Years**

(21) Appl. No.: **29/557,782**

(22) Filed: **Mar. 11, 2016**

(30) **Foreign Application Priority Data**

Sep. 15, 2015 (JP) 2015-020469

(51) **LOC (10) Cl.** **12-15**

(52) **U.S. Cl.**
USPC **D12/605**

(58) **Field of Classification Search**

USPC D12/500-605, 900; D5/30; D7/396.4,
D7/396.5, 588; 152/DIG. 12, 209.1,
152/209.8, 209.9, 209.12, 209.16, 209.26,
152/209.27, 517, 523, 524, 902, 903
CPC B60C 13/00; B60C 13/001; B60C 13/02;
B60C 1/00; B60C 1/0025; B60C 17/08
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D540,739 S * 4/2007 Maxwell D12/605
D542,220 S * 5/2007 Shondel D12/605
D581,352 S * 11/2008 Harvey D12/605
D581,353 S * 11/2008 Harvey D12/605
D581,354 S * 11/2008 Harvey D12/605
D590,332 S * 4/2009 Sato D12/605
D605,583 S * 12/2009 Scheifele D12/605
D618,163 S * 6/2010 Sato D12/605

D647,473 S * 10/2011 Kujime D12/605
D647,474 S * 10/2011 Takahashi D12/605
D655,671 S * 3/2012 Yasunaga D12/605
D708,121 S * 7/2014 Iwabuchi D12/605

(Continued)

FOREIGN PATENT DOCUMENTS

JP 1333102 6/2008
JP 1333103 6/2008

Primary Examiner — Wan Laymon

Assistant Examiner — Clint A Samuel

(74) *Attorney, Agent, or Firm* — Sterne, Kessler,
Goldstein & Fox P.L.L.C.

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire showing my new design;

FIG. 2 is a front view thereof;

FIG. 3 is a rear view thereof;

FIG. 4 is a top plan view thereof, the bottom plan view being a mirror image thereof;

FIG. 5 is a left side view thereof, the right side view being a mirror image thereof;

FIG. 6 is an enlarged view of the portion between 6-6 and 6'-6' in FIG. 2;


FIG. 7 is an enlarged cross-sectional view taken along line 7"-7" in FIG. 6 to line 7-7 in FIG. 4 within portion 7'-7' in FIG. 6;

FIG. 8 is an enlarged view of the portion between 8-8 and 8'-8' in FIG. 2; and,

FIG. 9 is an enlarged cross-sectional view taken along line 9'-9' in FIG. 8 to line 7-7 in FIG. 4 within portion 9-9 in FIG. 8.

In the drawings, the broken lines showing portions of the tire tread, sidewall, and inner bead depict portions of the tire that form no part of the claimed design.

1 Claim, 9 Drawing Sheets



(56) **References Cited**

U.S. PATENT DOCUMENTS

D711,816 S	*	8/2014	Iwabuchi	D12/605
D735,123 S	*	7/2015	Iwabuchi	D12/605
D735,124 S	*	7/2015	Iwabuchi	D12/605
D740,747 S	*	10/2015	Sato	D12/605
D750,553 S	*	3/2016	Scheifele	D12/605
D768,067 S	*	10/2016	Kuwano	D12/605
D768,565 S	*	10/2016	Yasunaga	D12/605
D773,985 S	*	12/2016	Sakamoto	D12/605
D773,986 S	*	12/2016	Nakamura	D12/605

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6



FIG. 7




FIG. 8




FIG. 9