

US00D792330S

(12) **United States Design Patent** (10) **Patent No.:** **US D792,330 S**
Haanketo et al. (45) **Date of Patent:** **** Jul. 18, 2017**

(54) **TYRE**

2200/14; B60C 7/00; B60C 7/02; B60C
7/04; B60C 7/06; B60C 7/08; B60C 5/00;
B60C 13/00

(71) Applicants: **Niko Haanketo**, Nokia (FI); **Tomi Korkama**, Tampere (FI); **Jorma Tikka**, Tampere (FI); **Outi Husso**, Sastamala (FI)

See application file for complete search history.

(72) Inventors: **Niko Haanketo**, Nokia (FI); **Tomi Korkama**, Tampere (FI); **Jorma Tikka**, Tampere (FI); **Outi Husso**, Sastamala (FI)

(56) **References Cited**

U.S. PATENT DOCUMENTS

D454,832	S	*	3/2002	Heinen		D12/550
D456,763	S	*	5/2002	Graas		D12/550
D462,647	S	*	9/2002	Heinen		D12/550
D471,147	S	*	3/2003	Kuwajima		D12/550
D595,220	S	*	6/2009	Maxwell		D12/590
D614,120	S	*	4/2010	Marella		D12/594
D660,222	S	*	5/2012	Kim		D12/519
D731,955	S	*	6/2015	Zhao		D12/519
D768,054	S	*	10/2016	Wang		D12/523
D769,793	S	*	10/2016	Haanketo		D12/523
D769,794	S	*	10/2016	Kujime		D12/523
2013/0146190	A1	*	6/2013	Aoki		B60C 11/0306 152/209.18

(73) Assignee: **NOKIAN TYRES PLC**, Nokia (FI)

(**) Term: **15 Years**

(21) Appl. No.: **29/555,189**

(22) Filed: **Feb. 19, 2016**

(30) **Foreign Application Priority Data**

Aug. 31, 2015 (EM) 002763243-0001
Aug. 31, 2015 (EM) 002763243-0002
Aug. 31, 2015 (EM) 002763243-0003

(51) **LOC (10) Cl.** **12-15**

(52) **U.S. Cl.**
USPC **D12/550; D12/523**

(58) **Field of Classification Search**

USPC 152/5, 151, 152.1, 167, 208,
152/209.1-209.28, 246, 450, 526, 527,
152/532, 535, 538, 541; D12/145,
D12/500-605, 900-901; D21/425-435,
D21/495

CPC B60C 11/00; B60C 2011/0337; B60C
2011/0339; B60C 2011/0386; B60C 3/00;
B60C 3/08; B60C 1/00; B60C 2200/00;
B60C 2200/02; B60C 2200/04; B60C
2200/06; B60C 2200/065; B60C 2200/08;
B60C 2200/10; B60C 2200/12; B60C

(Continued)

Primary Examiner — Manpreet Matharu

Assistant Examiner — Keith Wilson

(74) *Attorney, Agent, or Firm* — Klauber & Jackson LLC

(57) **CLAIM**

The ornamental design for a tyre, as shown and described.

DESCRIPTION

FIG. 1 is a front, left side perspective view of a tyre showing our new design;


FIG. 2 is a front elevation view thereof;

FIG. 3 is a left side view thereof, the right side view being the mirror image thereof;

FIG. 4 is a partial front elevational view taken from FIG. 2 and shown in an enlarged scale; and,

FIG. 5 is an enlarged fragmentary front view showing an individual cleat located on the right lateral edge of the tread.

1 Claim, 4 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0210121	A1 *	7/2015	Sanae	B60C 11/0304 152/209.8
2015/0231928	A1 *	8/2015	Sato	B60C 11/03 152/209.18
2016/0152087	A1 *	6/2016	Hayashi	B60C 11/1392 152/209.18
2016/0152090	A1 *	6/2016	Takemoto	B60C 11/0306 152/209.24

* cited by examiner



Fig. 1

FIG. 2






Fig. 3

FIG. 4




FIG. 5

