



US00D792493S

(12) **United States Design Patent** (10) **Patent No.:** **US D792,493 S**  
**Sato et al.** (45) **Date of Patent:** **\*\* Jul. 18, 2017**

(54) **ELECTRODE BAR FOR USE IN AN OPTICAL FIBER FUSION SPLICER**

(71) Applicant: **SEI Optifrontier Co., Ltd.**,  
Yokohama-shi, Kanagawa (JP)

(72) Inventors: **Ryuichiro Sato**, Yokohama (JP);  
**Toshihiko Homma**, Yokohama (JP)

(73) Assignee: **SEI Optifrontier Co., Ltd.**,  
Yokohama-shi, Kanagawa (JP)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/515,346**

(22) Filed: **Jan. 22, 2015**

(51) **LOC (10) Cl.** ..... **15-09**

(52) **U.S. Cl.**  
USPC ..... **D15/144.1**

(58) **Field of Classification Search**  
USPC .... D8/70, 382; D15/127, 144, 144.1, 144.2,  
D15/199  
CPC .. B23K 9/0026; G02B 6/2551; G02B 6/2553;  
G02B 6/2557; G02B 6/3616; G02B  
6/3636; G02B 6/3652; G02B 6/3696  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

D720,785 S \* 1/2015 Sato ..... D15/144.2

**FOREIGN PATENT DOCUMENTS**

JP	2000-137135 A	5/2000
JP	2000-249865 A	9/2000
JP	2003-167146 A	6/2003
JP	2005-234555 A	9/2005
JP	1479612	8/2013

**OTHER PUBLICATIONS**

Fujikura Data sheet, Mar. 26, 2008.\*  
2012 Optical Communication Product Catalog, p. 127, published by  
Fujikura, Ltd., Feb. 2012, Japan (with English Abstract).

\* cited by examiner

*Primary Examiner* — Patricia Palasik

(74) *Attorney, Agent, or Firm* — Drinker Biddle & Reath  
LLP

(57) **CLAIM**

The ornamental design for an electrode bar for an optical  
fiber fusion splicer, as shown and described.

**DESCRIPTION**

FIG. 1 is a front view of an electrode bar for an optical fiber  
fusion splicer of the present invention.

FIG. 2 is a rear view of the electrode bar for an optical fiber  
fusion splicer of FIG. 1.

FIG. 3 is a top plan view of the electrode bar for an optical  
fiber fusion splicer of FIG. 1.

FIG. 4 is a bottom view of the electrode bar for an optical  
fiber fusion splicer of FIG. 1.

FIG. 5 is a right side view of the electrode bar for an optical  
fiber fusion splicer of FIG. 1.


FIG. 6 is a left side view of the electrode bar for an optical  
fiber fusion splicer of FIG. 1.

FIG. 7 is a perspective view from above of the electrode bar  
for an optical fiber fusion splicer of FIG. 1; and,

FIG. 8 is a rear perspective view from below of the electrode  
bar for an optical fiber fusion splicer of FIG. 1.

The broken line showing is for the purpose of illustrating  
environmental structure and forms no part of the claimed  
design.

**1 Claim, 8 Drawing Sheets**






FIG. 1




FIG.2




FIG.3




FIG.4




FIG.5




FIG.6




FIG.7






FIG.8

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : D792,493 S  
APPLICATION NO. : 29/515346  
DATED : July 18, 2017  
INVENTOR(S) : Ryuichiro Sato et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the Title Page

(30) Foreign Application Priority Data should read:

--Jul. 29, 2014 (JP) 2014-016448--.

Signed and Sealed this  
Nineteenth Day of September, 2017



Joseph Matal  
*Performing the Functions and Duties of the  
Under Secretary of Commerce for Intellectual Property and  
Director of the United States Patent and Trademark Office*