



US00D799415S

(12) **United States Design Patent** (10) **Patent No.:** **US D799,415 S**
Sato (45) **Date of Patent:** **** Oct. 10, 2017**

(54) **TIRE**
(71) Applicant: **TOYO TIRE & RUBBER CO., LTD.**,
Osaka-shi, Osaka (JP)
(72) Inventor: **Yoshiki Sato**, Osaka (JP)
(73) Assignee: **Toyo Tire & Rubber Co., Ltd.**, Osaka
(JP)

D559,172 S * 1/2008 Umstot D12/605
D561,089 S * 2/2008 Maxwell D12/605
D563,311 S * 3/2008 Brainerd, II et al.
D577,329 S * 9/2008 Umstot D12/605
D577,661 S * 9/2008 Umstot D12/605
7,784,511 B2 * 8/2010 Harvey B60C 11/01
152/209.16
D663,259 S * 7/2012 Umstot D12/605
D772,798 S * 11/2016 Krier D12/605
D772,799 S * 11/2016 Shondel D12/605
D778,815 S * 2/2017 Emorine D12/605

(**) Term: **15 Years**

(Continued)

(21) Appl. No.: **29/559,664**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Mar. 30, 2016**

JP 1526575 S 6/2015

(30) **Foreign Application Priority Data**

Oct. 14, 2015 (JP) 2015-022655

Primary Examiner — Wan Laymon

Assistant Examiner — Clint A Samuel

(74) *Attorney, Agent, or Firm* — Sterne, Kessler,
Goldstein & Fox P.L.L.C.

(51) **LOC (10) Cl.** **12-15**

(52) **U.S. Cl.**
USPC **D12/605**

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

(58) **Field of Classification Search**
USPC D12/500-605, 900; D5/30; D7/396.4,
D7/396.5, 588; 152/DIG. 12, 209.1,
152/209.8, 209.9, 209.12, 209.16, 209.26,
152/209.27, 517, 523, 425, 902, 903
CPC B60C 13/00; B60C 13/001; B60C 13/02;
B60C 1/00; B60C 1/0025; B60C 17/08
See application file for complete search history.

DESCRIPTION


FIG. 1 is a perspective view of a tire showing my new design;
FIG. 2 is a front view thereof;
FIG. 3 is a rear view thereof;
FIG. 4 is a top plan view thereof;
FIG. 5 is a bottom plan view thereof;
FIG. 6 is a right side view thereof;
FIG. 7 is a left side view thereof;
FIG. 8 is an enlarged view of the portion 8-8 to line 8'-8' in FIG. 2; and,
FIG. 9 is an enlarged cross-sectional view taken along line 9'-9' in FIG. 8 to line 9-9 in FIG. 4.
In the drawings, the broken lines showing portions of the tire tread, sidewall, and inner bead depict portions of the tire that form no part of the claimed design.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D460,410 S * 7/2002 Thrasher D12/605
6,439,284 B1 * 8/2002 Fontaine B60C 11/0302
152/209.15
6,530,405 B1 * 3/2003 Brown B60C 11/01
152/209.16
6,533,007 B1 * 3/2003 McMannis B60C 11/01
152/209.16
D545,267 S * 6/2007 Umstot D12/605

1 Claim, 9 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2003/0041939	A1 *	3/2003	Allison	B60C 11/01 152/209.1
2005/0000616	A1 *	1/2005	Frantz	B29D 30/0061 152/524
2005/0167020	A1 *	8/2005	Rooney	B60C 11/0311 152/209.12
2008/0073018	A1 *	3/2008	Brei	B60C 11/00 152/524
2010/0043934	A1 *	2/2010	Harvey	B60C 11/01 152/209.16
2013/0139936	A1 *	6/2013	Ohara	B60C 13/02 152/209.11

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9