



US00D800643S

(12) **United States Design Patent** (10) **Patent No.:** **US D800,643 S**
Scheifele et al. (45) **Date of Patent:** **** Oct. 24, 2017**

- (54) **TIRE SIDEWALL**
- (71) Applicant: **Bridgestone Americas Tire Operations, LLC, Nashville, TN (US)**
- (72) Inventors: **Kevin E. Scheifele, Atwater, OH (US); David E. Schultz, Stow, OH (US); Keith A. Dumigan, Akron, OH (US)**
- (73) Assignee: **Bridgestone Americas Tire Operations, LLC, Nashville, TN (US)**
- (**) Term: **15 Years**
- (21) Appl. No.: **29/568,873**
- (22) Filed: **Jun. 22, 2016**

D479,190 S	9/2003	Maxwell	
D480,047 S	9/2003	Kajikawa	
D483,010 S	12/2003	Maxwell	
D492,648 S	7/2004	Maxwell et al.	
D497,593 S	10/2004	Ratliff, Jr. et al.	
D500,013 S	12/2004	Maxwell et al.	
D500,474 S	1/2005	Maxwell et al.	
D503,146 S	3/2005	Maxwell et al.	
D504,867 S	5/2005	Maxwell et al.	
D506,435 S	6/2005	Maxwell et al.	
D517,003 S	3/2006	Shondel	
D539,729 S	4/2007	Maxwell	
D540,250 S	4/2007	Shondel	
D540,739 S	4/2007	Maxwell	
D540,740 S	4/2007	Maxwell et al.	
D541,210 S	4/2007	Maxwell et al.	
D541,211 S	4/2007	Shondel et al.	
D542,219 S	5/2007	Shondel et al.	
D542,220 S	5/2007	Shondel et al.	
D543,496 S	5/2007	Shondel et al.	
D543,497 S	5/2007	Maxwell et al.	
D543,499 S	* 5/2007	Shondel	D12/605
D543,932 S	6/2007	Shondel	
D543,933 S	6/2007	Shondel	
D544,831 S	6/2007	Kikkawa et al.	
D547,261 S	7/2007	Shondel et al.	
D549,165 S	8/2007	Shondel et al.	
D549,166 S	8/2007	Lee	
D549,168 S	8/2007	Shondel et al.	
D550,149 S	9/2007	Shondel	
D550,150 S	9/2007	Shondel	
D550,151 S	9/2007	Maxwell	
D552,535 S	10/2007	Smith	
D552,536 S	10/2007	Shondel	
D552,537 S	10/2007	Franks et al.	
D555,583 S	11/2007	Itoi	
D557,202 S	12/2007	Shondel	
D558,138 S	12/2007	Shondel	
D561,089 S	2/2008	Maxwell	
D563,310 S	3/2008	Shondel	
D567,169 S	4/2008	Maxwell et al.	
D568,236 S	5/2008	Holden et al.	
D569,337 S	5/2008	Iwabuchi	
D569,338 S	5/2008	Shondel	
D569,792 S	5/2008	Holden et al.	
D569,793 S	5/2008	Dixon	
D570,768 S	6/2008	Takahashi	
D571,287 S	6/2008	Dixon	
D574,320 S	8/2008	Dixon	
7,409,975 B2	8/2008	Wallet	
D579,867 S	* 11/2008	Behr	D12/605
D581,352 S	11/2008	Harvey	
D581,353 S	11/2008	Harvey	


Related U.S. Application Data

- (63) Continuation-in-part of application No. 29/503,977, filed on Oct. 1, 2014, now abandoned.
- (51) **LOC (10) Cl.** **12-15**
- (52) **U.S. Cl.**
USPC **D12/605**
- (58) **Field of Classification Search**
USPC D12/500-605, 900
CPC B60C 1/00; B60C 13/00; B60C 13/02
See application file for complete search history.

References Cited

U.S. PATENT DOCUMENTS

D379,168 S	5/1997	Ratliff, Jr.
D380,718 S	7/1997	Ratliff, Jr.
5,645,661 A	7/1997	Clementz et al.
D385,834 S	11/1997	Ratliff, Jr.
D386,455 S	11/1997	Clementz et al.
5,807,446 A	9/1998	Ratliff, Jr.
D412,476 S	8/1999	Clementz et al.
D413,289 S	8/1999	Ratliff, Jr. et al.
D449,576 S	10/2001	Kajikawa
D450,034 S	11/2001	Kajikawa
D450,274 S	11/2001	Ratliff, Jr. et al.
D450,275 S	11/2001	Moses
D452,203 S	12/2001	Kajikawa
D457,130 S	5/2002	Ratliff, Jr. et al.



D581,354 S	11/2008	Harvey	
D583,313 S	12/2008	Harvey	
D585,016 S	1/2009	Weimer et al.	
D585,017 S	1/2009	Shondel	
D585,018 S	1/2009	Shondel	
D588,529 S	3/2009	Reese et al.	
D588,532 S	3/2009	Shondel	
D593,487 S	6/2009	Takahashi	
D593,939 S	6/2009	Maxwell	
D596,119 S	7/2009	Fujita	
D597,025 S	7/2009	Fujita	
D599,284 S	9/2009	Misumi	
D605,583 S	12/2009	Scheifele	
D606,013 S	12/2009	Reese et al.	
D606,014 S	12/2009	Kujime	
D606,015 S	12/2009	Kujime	
D606,016 S	12/2009	Scheifele	
D606,488 S	12/2009	Scheifele	
D606,933 S	12/2009	Palma et al.	
D608,273 S	1/2010	Scheifele et al.	
D608,274 S	1/2010	Takahashi	
D608,275 S	1/2010	Maxwell	
D610,978 S	3/2010	Harvey et al.	
D610,980 S	3/2010	Shondel	
D610,981 S	3/2010	Shondel	
D612,802 S	3/2010	Nakamura	
D614,123 S	4/2010	Harvey	
D628,959 S	12/2010	Harvey	
D629,745 S	12/2010	Shondel	
D638,783 S	5/2011	Endou et al.	
D638,784 S	5/2011	Scheifele	
D639,728 S	* 6/2011	Ohashi	D12/605
D640,186 S	6/2011	Miyazaki	
D640,187 S	6/2011	Fontaine et al.	
D647,044 S	10/2011	Takemoto	
D650,323 S	12/2011	Morito et al.	
D656,089 S	3/2012	Miyazaki	
D656,090 S	3/2012	Sato	
D662,039 S	6/2012	Miyasaka et al.	
D662,465 S	6/2012	Takano	
D662,871 S	7/2012	Miyazaki	
D662,877 S	7/2012	Arrant et al.	
D666,143 S	8/2012	Sato	
D667,369 S	9/2012	Fontaine et al.	
D667,782 S	9/2012	Mukai	
D671,067 S	11/2012	Yasunaga	
D676,805 S	* 2/2013	Iwabuchi	D12/605
8,381,786 B2	2/2013	Ebiko et al.	
D677,217 S	* 3/2013	Iwabuchi	D12/605
D678,832 S	3/2013	Fontaine et al.	
D680,490 S	4/2013	Iwabuchi	
D681,546 S	5/2013	Sato	
D681,547 S	5/2013	Sato	
D682,191 S	5/2013	Ebiko et al.	
D683,303 S	5/2013	Ebiko et al.	
D684,110 S	6/2013	Frappart et al.	
D684,111 S	* 6/2013	Vandaele	D12/605
D693,761 S	11/2013	Nakamura	
D699,665 S	2/2014	Maxwell et al.	
D700,886 S	3/2014	Matsumoto et al.	
D701,826 S	4/2014	Morito et al.	
D707,621 S	6/2014	Tokizaki et al.	
D726,645 S	* 4/2015	Scheifele	D12/605
D730,819 S	* 6/2015	Scheifele	D12/605
D734,716 S	* 7/2015	Rittweger	D12/605
D735,652 S	* 8/2015	Rittweger	D12/605
2005/0081975 A1	4/2005	Sano	
2006/0254689 A1	11/2006	Wallet	
2013/0146196 A1	6/2013	Shibayama	

* cited by examiner

Primary Examiner — Robert M Spear

Assistant Examiner — John Voytek

(74) Attorney, Agent, or Firm — Shaun J. Fox

(57) CLAIM

The ornamental design for a tire sidewall, as shown and described.

DESCRIPTION

FIG. 1 is a side elevational view of a first, second, and third embodiment of our new tire sidewall design;
 FIG. 2 is a cross-sectional view along cross-section line A-A of FIG. 1 of a first embodiment of our new tire sidewall design;
 FIG. 3 is cross-sectional view along cross-section line A-A of FIG. 1 a second embodiment of our new tire sidewall design;
 FIG. 4 is cross-sectional view along cross-section line A-A of FIG. 1 of a third embodiment of our new tire sidewall design;
 FIG. 5 is a side elevational view of a fourth, fifth, sixth, and seventh embodiment of our new tire sidewall sidewall design;
 FIG. 6 is a cross-sectional view along cross-section line B-B of FIG. 5 of a fourth embodiment of our new tire sidewall design;
 FIG. 7 is a cross-sectional view along cross-section line B-B of FIG. 5 of a fifth embodiment of our new tire sidewall design;
 FIG. 8 is a cross-sectional view along cross-section line B-B of FIG. 5 of a sixth embodiment of our new tire sidewall design;
 FIG. 9 is a cross-sectional view along cross-section line B-B of FIG. 5 of a seventh embodiment of our new tire sidewall design;
 FIG. 10 is a side elevational view of an eighth, ninth, and tenth embodiment of our new tire sidewall design;
 FIG. 11 is a cross-sectional view along cross-section line C-C of FIG. 10 of an eighth embodiment of our new tire sidewall design;
 FIG. 12 is a cross-sectional view along cross-section line C-C of FIG. 10 of a ninth embodiment of our new tire sidewall design;
 FIG. 13 is a cross-sectional view along cross-section line C-C of FIG. 10 of a tenth embodiment of our new tire sidewall design;
 FIG. 14 is a side elevational view of an eleventh, twelfth, thirteenth, and fourteenth embodiment of our new tire sidewall design;
 FIG. 15 is a cross-sectional view along cross-section line D-D of FIG. 14 of an eleventh embodiment of our new tire sidewall design;
 FIG. 16 is a cross-sectional view along cross-section line D-D of FIG. 14 of a twelfth embodiment of our new tire sidewall design;
 FIG. 17 is a cross-sectional view along cross-section line D-D of FIG. 14 of a thirteenth embodiment of our new tire sidewall design;
 FIG. 18 is a cross-sectional view along cross-section line D-D of FIG. 14 of a fourteenth embodiment of our new tire sidewall design;
 FIG. 19 is a side elevational view of a fifteenth, sixteenth, and seventeenth embodiment of our new tire sidewall design;
 FIG. 20 is a cross-sectional view along cross-section line E-E of FIG. 19 of a fifteenth embodiment of our new tire sidewall design;

FIG. **21** is a cross-sectional view along cross-section line E-E of FIG. **19** of a sixteenth embodiment of our new tire sidewall design;

FIG. **22** is a cross-sectional view along cross-section line E-E of FIG. **19** of a seventeenth embodiment of our new tire sidewall design;

FIG. **23** is a side elevational view of a eighteenth, nineteenth, and twentieth embodiment of our new tire sidewall design;

FIG. **24** is a cross-sectional view along cross-section line F-F of FIG. **23** of an eighteenth embodiment of our new tire sidewall design;

FIG. **25** is a cross-sectional view along cross-section line F-F of FIG. **23** of a nineteenth embodiment of our new tire sidewall design; and,

FIG. **26** is a cross-sectional view along cross-section line F-F of FIG. **23** of a twentieth embodiment of our new tire sidewall design.

The varied broken lines defining the tire tread, inner bead, inner bead, and portions of the tire sidewall represent unclaimed environmental subject matter; the broken lines immediately adjacent the shaded surfaces of the tire sidewall represent the boundaries of the claimed design but form no part thereof.

1 Claim, 26 Drawing Sheets




FIG. 1




FIG.2




FIG. 3




FIG.4




FIG. 5




FIG.6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG.20




FIG.21




FIG. 22




FIG. 23




FIG.24




FIG. 25




FIG. 26