

US00D804924S

(12) **United States Design Patent** (10) **Patent No.:** **US D804,924 S**
Iijima et al. (45) **Date of Patent:** **** Dec. 12, 2017**

(54) **TRIGGER FOR NAILER**

(71) Applicant: **Hitachi Koki Co., Ltd.**, Minato-Ku,
Tokyo (JP)

(72) Inventors: **Yoshimitsu Iijima**, Hitachinaka (JP);
Masaaki Furumi, Hitachinaka (JP)

(73) Assignee: **Hitachi Koki Co., Ltd.**, Minato-Ku,
Tokyo (JP)

(**) Term: **15 Years**

(21) Appl. No.: **29/573,819**

(22) Filed: **Aug. 10, 2016**

(30) **Foreign Application Priority Data**

Feb. 10, 2016 (JP) 2016-002860

(51) **LOC (10) Cl.** **08-05**

(52) **U.S. Cl.**
USPC **D8/70**

(58) **Field of Classification Search**

USPC D7/393, 394, 395, 398; D8/61, 68, 69,
D8/70, 302, 306, 308, 309, 315, 317,
D8/319; D11/116, 133, 203;
D12/177-178; D19/96; D22/103-104,
D22/108; D23/226, 249, 304; D26/7,
D26/13, 15, 17, 31, 42

CPC F41A 19/10; F41A 19/12; F41A 19/44;
F41A 19/31; E05B 1/00; E05B 1/0015;
H01H 9/06; H01H 9/061

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D301,199 S * 5/1989 Zurwelle D8/70
D371,591 S * 7/1996 Lenkarski D22/100

D399,914 S * 10/1998 Walker D21/572
D417,151 S * 11/1999 Spengler D9/448
D421,718 S * 3/2000 Durliat D9/434
D454,306 S * 3/2002 Sweeton D9/434
6,415,958 B1 * 7/2002 Donley B05B 12/00
222/146.5
D462,105 S * 8/2002 Myers D22/108
6,615,527 B1 * 9/2003 Martin F41A 19/46
42/20
D488,968 S * 4/2004 Kinerson D8/30
D504,493 S * 4/2005 Huang D23/226
D505,072 S * 5/2005 Turnbull D9/448
D540,431 S * 4/2007 Turnbull D23/226
D562,435 S * 2/2008 Turnbull D23/226
7,331,136 B2 * 2/2008 Geissele F41A 19/16
42/69.03
D597,626 S * 8/2009 Krieger D22/108
D624,609 S * 9/2010 Stein D21/573
8,220,193 B1 * 7/2012 Lynch F41A 17/48
42/70.08
8,250,799 B2 * 8/2012 Duperry F41A 19/10
42/42.02

(Continued)

Primary Examiner — Darlington Ly

(74) *Attorney, Agent, or Firm* — Banner & Witcoff, Ltd.

(57) **CLAIM**

The ornamental design for a trigger for a nailer, as shown
and described.

DESCRIPTION

FIG. 1 is a front elevation view of a trigger for a nailer
showing our new design;

FIG. 2 is a rear elevation view thereof;

FIG. 3 is a left side elevation view thereof;


FIG. 4 is a right side elevation view thereof;

FIG. 5 is a top plan view thereof;

FIG. 6 is a bottom plan view thereof; and,

FIG. 7 is a top, front, and right side perspective view thereof,
while in a state in which a moving member has been moved.

1 Claim, 4 Drawing Sheets



(56) **References Cited**

U.S. PATENT DOCUMENTS

8,667,881	B1 *	3/2014	Hawbaker		F41A 19/45
					42/69.01
D740,907	S *	10/2015	Oglesby		D22/108
D764,004	S *	8/2016	Bender		D22/108
D777,285	S *	1/2017	Bender		D22/108
D786,402	S *	5/2017	Rose		D23/226
D791,916	S *	7/2017	Rose		D23/226
2016/0131448	A1 *	5/2016	Bender		F41A 19/10
					42/69.01

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

