



US00D805567S

(12) **United States Design Patent**  
**Kita**

(10) **Patent No.:** **US D805,567 S**

(45) **Date of Patent:** **\*\* Dec. 19, 2017**

(54) **GRIP FOR DESOLDERING TOOL**

(71) Applicant: **Hakko Corporation**,  
Naniwa-ku,Osaka-shi,Osaka (JP)

(72) Inventor: **Toshiyuki Kita**, Osaka (JP)

(73) Assignee: **HAKKO CORPORATION**, Osaka  
(JP)

(\*\*) Term: **15 Years**

(21) Appl. No.: **29/557,234**

(22) Filed: **Mar. 7, 2016**

(30) **Foreign Application Priority Data**

Nov. 27, 2015 (JP) ..... D2015-026447

(51) **LOC (10) Cl.** ..... **15-09**

(52) **U.S. Cl.**  
USPC ..... **D15/144.2**; D8/30

(58) **Field of Classification Search**  
USPC ..... D8/14, 29.1, 29.2, 30, 68; D15/144,  
D15/144.1, 144.2  
CPC . B23K 1/018; B23K 1/08; B23K 3/00; B23K  
3/02

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

- 4,574,994 A \* 3/1986 Rauchwerger ..... B23K 1/018  
228/20.5
- D289,004 S \* 3/1987 Somers ..... D8/68
- D293,201 S \* 12/1987 House, II ..... D8/68
- 5,007,574 A \* 4/1991 Carlomagno ..... B23K 1/018  
219/236
- 5,143,272 A \* 9/1992 Carlomagno ..... B23K 3/029  
228/20.5
- D406,737 S \* 3/1999 Farnham ..... D8/29.1
- D456,684 S \* 5/2002 Izumisawa ..... D8/62

- D459,182 S \* 6/2002 Morgan ..... D8/68
- D481,280 S \* 10/2003 Guiette, III ..... D8/68
- 6,887,146 B2 \* 5/2005 Staas ..... B23Q 11/0046  
144/252.1
- D514,408 S \* 2/2006 Melendy ..... D8/14.1
- D514,413 S \* 2/2006 Cuenca ..... D8/68
- D740,091 S \* 10/2015 Mochizuki ..... D8/30
- D765,482 S \* 9/2016 Kita ..... D8/30
- D782,005 S \* 3/2017 Naslund ..... D23/223
- D790,940 S \* 7/2017 Dill ..... D8/68
- 2003/0224707 A1 \* 12/2003 Segiel, Jr. .... B23Q 11/0046  
451/451

**OTHER PUBLICATIONS**

Hakko Corporation, Catalog showing product information, published May 2014.

\* cited by examiner

*Primary Examiner* — Patricia Palasik

(74) *Attorney, Agent, or Firm* — Squire Patton Boggs  
(US) LLP


(57) **CLAIM**

The ornamental design for a grip for desoldering tool, as shown and described.

**DESCRIPTION**

FIG. 1 is a first perspective view of a grip for desoldering tool;  
 FIG. 2 is a second perspective view thereof;  
 FIG. 3 is a front view thereof;  
 FIG. 4 is a rear view thereof;  
 FIG. 5 is a left side view thereof;  
 FIG. 6 is a right side view thereof;  
 FIG. 7 is a top view thereof; and,  
 FIG. 8 is a bottom view thereof.  
 The broken lines depict unclaimed environmental subject matter of the grip for desoldering tool.

**1 Claim, 6 Drawing Sheets**






FIG.1




FIG.2




FIG.3




FIG.4




FIG. 5




FIG. 6




FIG.7




FIG.8