



US00D805879S

(12) **United States Design Patent**
Garcia

(10) **Patent No.:** **US D805,879 S**

(45) **Date of Patent:** **** Dec. 26, 2017**

(54) **CORD TENSIONING AND SECURING DEVICE**

(71) Applicant: **Brent A. Garcia**, Las Vegas, NV (US)

(72) Inventor: **Brent A. Garcia**, Las Vegas, NV (US)

(**) Term: **15 Years**

(21) Appl. No.: **29/560,632**

(22) Filed: **Apr. 8, 2016**

(51) **LOC (10) Cl.** **09-06**

(52) **U.S. Cl.**
USPC **D8/356**

(58) **Field of Classification Search**
USPC D8/356, 354, 349
CPC B65H 57/16; E02D 5/803; B63B 21/045;
B63B 59/02; B60D 1/18; B60P 1/103;
Y10T 24/3918
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,229,935	A	1/1941	Powers	
2,937,833	A *	5/1960	Sachs	F16L 3/2235 248/49
4,099,626	A *	7/1978	Magnussen, Jr.	A47B 63/02 211/194
D258,864	S *	4/1981	Muller	D8/356
D265,052	S *	6/1982	Husted	D8/356
5,234,185	A *	8/1993	Hoffman	F16L 5/14 248/56
5,316,246	A *	5/1994	Scott	A61M 5/1418 248/68.1
D353,990	S *	1/1995	Alfreds	D8/356
D372,188	S *	7/1996	Van Dyke	D8/358
D390,447	S *	2/1998	Colen, Jr.	D8/356
5,992,802	A *	11/1999	Campbell	F16L 3/2235 248/68.1

6,571,854	B1 *	6/2003	Palmer	E06B 9/324 160/173 R
D494,450	S *	8/2004	Schultz	D8/356
7,081,004	B1	7/2006	Puzio	
D576,867	S *	9/2008	Kretz	D8/356
7,610,661	B2 *	11/2009	Sween	B65H 75/06 24/129 R
8,294,030	B2 *	10/2012	Pollard, Jr.	H02G 3/24 174/155
D731,296	S *	6/2015	Nelson	D8/356
D753,985	S *	4/2016	Nelson	D8/356
D791,582	S *	7/2017	Nelson	D8/356
D794,434	S *	8/2017	McCoy	D8/354
9,755,354	B1 *	9/2017	Aumiller	H01R 13/60

* cited by examiner

Primary Examiner — Cynthia Underwood
(74) *Attorney, Agent, or Firm* — Loza & Loza, LLP;
Heidi L. Eisenhut


(57) **CLAIM**

The ornamental design for a cord tensioning and securing device, substantially as shown and described.

DESCRIPTION

The present application is a continuation, and claims the priority benefit of, U.S. patent application Ser. No. 14/152,077 filed Jan. 10, 2014, the contents of which are hereby incorporated in their entirety into the present disclosure. FIG. 1 is a perspective view of a cord tensioning and securing device in accordance with the present invention; FIG. 2 is a left side view thereof; FIG. 3 is a right side view thereof; and, FIG. 4 is a bottom perspective view thereof. The broken lines represent portions of the structure that forms no part of the claim.

1 Claim, 4 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4