

US00D806008S

(12) **United States Design Patent** (10) **Patent No.:** **US D806,008 S**
Marella et al. (45) **Date of Patent:** **** Dec. 26, 2017**

(54) **TIRE TREAD SHOULDER**

(71) Applicant: **Bridgestone Americas Tire Operations, LLC**, Nashville, TN (US)

(72) Inventors: **Anthony R. Marella**, Tallmadge, OH (US); **Kevin E. Scheifele**, Atwater, OH (US)

(73) Assignee: **Bridgestone Americas Tire Operations, LLC**, Nashville, TN (US)

(**) Term: **15 Years**

(21) Appl. No.: **29/554,377**

(22) Filed: **Feb. 11, 2016**

(51) **LOC (10) Cl.** **12-15**

(52) **U.S. Cl.**
USPC **D12/605**

(58) **Field of Classification Search**
USPC D12/500–605, 900; D5/30; D7/396.4, D7/396.5, 588; 152/DIG. 12, 209.1, 152/209.8, 209.9, 209.12, 209.16, 209.26, 152/209.27, 517, 523, 524, 902, 903
CPC B60C 13/00; B60C 13/001; B60C 13/02; B60C 1/00; B60C 1/0025; B60C 17/08
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D313,777 S *	1/1991	Yamashita		D12/596
D447,449 S *	9/2001	Guspodin		D12/605
D450,635 S	11/2001	Fierro et al.		
D451,455 S	12/2001	Helt		
D452,199 S	12/2001	Robert et al.		
D454,331 S	3/2002	Fierro et al.		
D459,696 S	7/2002	Robert et al.		
D500,473 S *	1/2005	Boggs		D12/605
D554,055 S	10/2007	Beauguitte et al.		
D575,727 S *	8/2008	Shondel		D12/605

D577,329 S *	9/2008	Umstot		D12/605
D577,331 S *	9/2008	Ochi		D12/605
D577,661 S *	9/2008	Umstot		D12/605
D592,589 S	5/2009	Dixon et al.		
D595,643 S *	7/2009	Ochi		D12/605
D596,111 S	7/2009	Miyazaki		
D600,635 S	9/2009	Finnell et al.		
D615,031 S *	5/2010	Osaka		D12/605
D639,234 S	6/2011	Reim		
D639,235 S	6/2011	Reim et al.		
D663,259 S *	7/2012	Umstot		D12/605
D673,899 S	1/2013	Uphouse et al.		
D674,743 S	1/2013	Uphouse et al.		
D700,885 S	3/2014	Le et al.		

(Continued)

Primary Examiner — Wan Laymon

Assistant Examiner — Clint A Samuel

(74) *Attorney, Agent, or Firm* — Shaun J. Fox

(57) **CLAIM**

The ornamental design for a tire tread shoulder, as shown and described.

DESCRIPTION

FIG. 1 is a side perspective view of a tire tread shoulder showing our new design, it being understood that the pattern is repeated throughout the circumference of the tire, the opposite side being the same as that shown;

FIG. 2 is a side elevational view thereof, the opposite side being identical thereto;

FIG. 3 is a front elevational view and the opposite side being the same as that shown;


FIG. 4 is an enlarged fragmentary side elevational view thereof;

FIG. 5 is an enlarged fragmentary view thereof; and,

FIG. 6 is an enlarged fragmentary view thereof.

The regular dash lines are included for the purpose of illustrating portions of the tire tread shoulder that form no part of the claimed design. The bold dot-dash-dot lines represent boundaries of the claimed design.

1 Claim, 5 Drawing Sheets



(56) **References Cited**

U.S. PATENT DOCUMENTS

D738,294	S	9/2015	Koog	
D738,813	S	9/2015	Wang	
D738,814	S	9/2015	Otani	
D771,558	S	*	11/2016	Krier D12/605
D776,046	S	*	1/2017	Dixon D12/605

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6