



US00D806146S

(12) **United States Design Patent** (10) **Patent No.:** **US D806,146 S**
Messerli (45) **Date of Patent:** **** Dec. 26, 2017**

(54) **MACHINE COVER**

DESCRIPTION

(71) Applicant: **Schleuniger Holding AG**, Thun (CH)

(72) Inventor: **Jolanda Messerli**, Lyss (CH)

(73) Assignee: **Schleuniger Holding AG**, Thun (CH)

(**) Term: **15 Years**

(21) Appl. No.: **29/561,776**

(22) Filed: **Apr. 20, 2016**

Related U.S. Application Data

(63) Continuation-in-part of application No. 29/417,692, filed on Apr. 6, 2012, now abandoned.

(30) **Foreign Application Priority Data**

Nov. 11, 2011 (CH) 636 502 601

(51) **LOC (10) Cl.** **15-09**

(52) **U.S. Cl.**
USPC **D15/122**

(58) **Field of Classification Search**
USPC D15/122, 138

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,259,173 A * 7/1966 Manning B41J 29/13
150/154
3,899,043 A * 8/1975 Hall G10K 11/16
181/200

(Continued)

Primary Examiner — Patricia A Palasik

(74) *Attorney, Agent, or Firm* — Matthew B. Dernier, Esq.

(57) **CLAIM**

The ornamental design for a machine cover, as shown and described.

FIG. 1 is a front-perspective view of the machine cover on a machine, where the machine cover is at least semi-transparent in a generally central region and gradually becomes opaque toward edges thereof, where the machine is shown in broken lines for illustrative purposes (showing environment only and forms no part of the claimed design), and where the machine cover is shown in a closed position over the machine;

FIG. 2 is a front view of the machine cover of FIG. 1, where the machine cover is at least semi-transparent in a generally central region and gradually becomes opaque toward edges thereof;

FIG. 3 is a rear view of the machine cover of FIG. 1, where the feature of the at least semi-transparent central region and gradual transition to opaque toward the edges thereof may also be seen owing to the at least semi-transparent nature of the material from which the machine cover is made, where left and right edges showing a relative thickness of the machine cover are visible, and where the gradual change from at least semi-transparent to opaque is illustrated with reference to FIG. 8, which shows a magnified view of the transition;

FIG. 4 is a left view of the machine cover of FIG. 1;

FIG. 5 is a right view of the machine cover of FIG. 1;


FIG. 6 is a top view of the machine cover of FIG. 1;

FIG. 7 is a bottom view of the machine cover of FIG. 1; and,

FIG. 8 is an enlarged view of the portion in rectangle 8 of FIG. 3, showing the gradual transition from opaque at an edge of the machine cover toward the at least semitransparent central region of the machine cover, where the gradual transition is formed from a gradually changing density of opaque dots from the opaque edge of the machine cover (with a highest density of dots) toward the at least semi-transparent region of the machine cover (with a reducing density of dots), and where such detail also applies to the other illustrated gradual transitions from opaque to at least semi-transparent in other portions of FIG. 3 and the other views of the machine cover.

To the extent not already stated, the broken lines of the drawing are for illustrative purposes, showing environment only, and form no part of the claimed design.

1 Claim, 8 Drawing Sheets



(58) **Field of Classification Search**

CPC B41J 29/13; B65D 65/22; B65D 85/68;
D21F 1/0027

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D438,563 S *	3/2001	Webb	D19/10
6,773,786 B1 *	8/2004	Kuckart	D21F 1/0027
				34/111
D777,502 S *	1/2017	Fuller	D7/339
D796,314 S *	9/2017	Riffe	D9/414
2014/0102606 A1 *	4/2014	Brehm	B65D 65/22
				150/154

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5



FIG. 6



FIG. 7




FIG. 8