



US00D806500S

(12) **United States Design Patent**
Castillo et al.

(10) **Patent No.:** **US D806,500 S**
(45) **Date of Patent:** **** Jan. 2, 2018**

(54) **SAFETY HANDLE**

(71) Applicant: **TryThisFirst, Inc.**, Walnut Creek, CA (US)

(72) Inventors: **Bradley Castillo**, San Ramon, CA (US); **Scott Morehouse**, Berkeley, CA (US); **Gordon L. Rogers**, Walnut Creek, CA (US)

(73) Assignee: **TryThisFirst, Inc.**, Walnut Creek, CA (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/511,281**

(22) Filed: **Dec. 9, 2014**

(51) **LOC (11) Cl.** **08-01**

(52) **U.S. Cl.**
USPC **D8/107**

(58) **Field of Classification Search**
USPC D8/80, 82, 83, 84, 85, 86, 87, 107, 300, D8/303, 307; D7/393, 395; 16/110.1, 16/421, 429, 430, 431; 81/177.1, 177.85, 81/489
CPC Y10T 16/469; Y10T 16/44; Y10T 16/476; Y10T 16/473; Y10T 74/2078; Y10T 74/20828; Y10T 16/498; Y10T 16/466; Y10T 16/506; Y10T 16/513; Y10T 16/4719; Y10T 16/46; Y10T 16/4713; Y10T 74/20792; Y10T 16/4559; Y10T 74/20732; Y10T 16/4707; Y10T 403/32475; Y10T 16/455; Y10T 16/4571; Y10T 74/20876; Y10T 74/20864; Y10T 16/4554; Y10T 16/509; Y10T 74/2087; Y10T 16/459; Y10T 16/4563; Y10T 74/20612; Y10T 16/4567; Y10T 16/4644; Y10T 16/4636; Y10S 16/12; Y10S 16/30; Y10S 16/24; Y10S 16/19; Y10S 16/90; Y10S 16/41; Y10S 16/902; Y10S 16/40;

Y10S 16/903; Y10S 16/904; Y10S 16/25; Y10S 16/901; Y10S 292/31; Y10S 56/18

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D368,999	S	*	4/1996	Chen	D32/48
D440,048	S		4/2001	Beals et al.		
D459,051	S		6/2002	Weiss et al.		
6,557,212	B2	*	5/2003	Huang	B25G 3/26 15/145
D517,393	S	*	3/2006	Chen	D32/48
D517,895	S	*	3/2006	Chen	D32/48
D520,844	S	*	5/2006	Chen	D32/48
D552,444	S	*	10/2007	Cybulski	D8/300
7,311,023	B2	*	12/2007	Ponzini	A61C 15/046 16/422

(Continued)

Primary Examiner — Lauren Calve

(74) *Attorney, Agent, or Firm* — EIP US LLP

(57) **CLAIM**



We claim the ornamental design for a safety handle, as shown and described.

DESCRIPTION

FIG. 1 is a top plan view of a safety handle according to the present design;
FIG. 2 is a bottom plan view thereof;
FIG. 3 is a top perspective view thereof;
FIG. 4 is a bottom perspective view thereof;
FIG. 5 is a side elevation view thereof;
FIG. 6 is an opposite side elevation view thereof;
FIG. 7 is a front elevation view thereof;
FIG. 8 is a back elevation view thereof; and,
FIG. 9 is a cross-sectional view thereof taken along lines 9-9 shown in FIG. 1.

The dash-dot-dash lines shown represent the plane upon which the cross-sectional view is taken and form no part of the claimed design.

1 Claim, 5 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D561,527 S *	2/2008	Giannone	D7/395
D583,211 S *	12/2008	Grohmann	D8/300
D608,139 S *	1/2010	Rae	D7/395
D614,471 S *	4/2010	Meyer	D8/107
D630,470 S *	1/2011	McEldowney	D7/395
D667,264 S *	9/2012	Rae	D7/395
D686,796 S	7/2013	Deutschman	
8,573,438 B1 *	11/2013	Cheng	A47J 45/071 16/422
D703,377 S	4/2014	Christie et al.	
D710,542 S	8/2014	Eagleton et al.	
2003/0217437 A1 *	11/2003	Chen	B25G 3/26 16/422
2005/0273959 A1 *	12/2005	Dillon	A46B 5/00 15/144.1
2009/0188061 A1 *	7/2009	Cybulski	A47J 37/0786 15/111

* cited by examiner




FIG. 1




FIG. 2

FIG. 3




FIG. 4




FIG. 5




FIG. 7




FIG. 6




FIG. 8




FIG. 9