

US00D806752S

(12) **United States Design Patent** (10) **Patent No.:** **US D806,752 S**
Vaninetti et al. (45) **Date of Patent:** **** Jan. 2, 2018**

(54) **TILLER HAVING HAPTIC THROTTLE POSITION INDICATION**

(71) Applicant: **Brunswick Corporation**, Lake Forest, IL (US)

(72) Inventors: **Travis J. Vaninetti**, Neenah, WI (US);
Todd D. Dannenberg, Fond du Lac, WI (US)

(73) Assignee: **Brunswick Corporation**, Mettawa, IL (US)

(**) Term: **15 Years**

(21) Appl. No.: **29/608,748**

(22) Filed: **Jun. 26, 2017**

Related U.S. Application Data

(62) Division of application No. 29/576,397, filed on Sep. 2, 2016, now Pat. No. Des. 794,079.

(51) **LOC (11) Cl.** **15-01**

(52) **U.S. Cl.**
USPC **D15/4**

(58) **Field of Classification Search**

USPC D15/4, 5; 114/114 R, 146; 74/480 B,
74/483 R, 491, 492, 481, 523, 543;
D12/317; 440/84, 86, 87, 63, 53
CPC B63H 21/213; B63H 21/00; B63H 21/22;
B63H 20/007; B63H 20/00; B63H 20/10;
B63H 20/12; B63H 25/42

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,636,911 A 1/1972 Piazza
D276,811 S 12/1984 Wolfe
4,496,326 A 1/1985 Boda
4,521,201 A 6/1985 Watanabe

4,582,493 A 4/1986 Toyohara
4,650,429 A 3/1987 Boda
4,701,141 A 10/1987 Sumigawa
D295,867 S 5/1988 Walsh
4,878,468 A 11/1989 Boda et al.
5,340,342 A 8/1994 Boda et al.
5,632,657 A 5/1997 Henderson
D380,478 S 7/1997 Robbins
6,010,563 A 2/2000 Risk, Jr.
6,093,066 A 7/2000 Isogawa
6,146,221 A 11/2000 Natsume
6,264,516 B1 7/2001 McEathron et al.
6,406,342 B1 6/2002 Walczak et al.
6,902,450 B2 6/2005 Ohtsuki
7,090,551 B1 8/2006 Lokken et al.
D527,737 S 9/2006 Iekura
7,214,113 B2 5/2007 Kojima
D552,129 S 10/2007 Steinberg
7,455,558 B2 11/2008 Yander
D611,501 S 3/2010 Vignau et al.

(Continued)

Primary Examiner — Mark Goodwin

(74) *Attorney, Agent, or Firm* — Andrus Intellectual Property Law, LLP

(57) **CLAIM**

The ornamental design for a tiller having haptic throttle position indication, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tiller having haptic throttle position indication showing our new design.

FIG. 2 is a left side view thereof.

FIG. 3 is a right side view thereof.

FIG. 4 is a front end view thereof.


FIG. 5 is a rear end view thereof.

FIG. 6 is a top view thereof; and,

FIG. 7 is a bottom view thereof.

Portions of the tiller which are shown in broken line are for illustrative purposes only and form no part of the claimed design.


1 Claim, 4 Drawing Sheets



(56) **References Cited**

U.S. PATENT DOCUMENTS

D611,502 S	3/2010	Vignau et al.
7,677,938 B2	3/2010	Wiatrowski et al.
7,704,110 B2	4/2010	Wiatrowski et al.
7,895,959 B1	3/2011	Angel et al.
D655,308 S	3/2012	Steinberg
8,257,122 B1	9/2012	Holley
9,422,045 B2	8/2016	Kinpara






FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7