



US00D817486S

(12) **United States Design Patent** (10) **Patent No.:** **US D817,486 S**
Corato et al. (45) **Date of Patent:** **** May 8, 2018**

(54) **LINE MANAGEMENT DEVICE FOR
RETAINING AND POSITIONING WIRES
AND TUBES**

(71) Applicant: **JMC Global Technologies I, L.P.**,
Keller, TX (US)

(72) Inventors: **Craig Douglas Corato**, Keller, TX
(US); **Huy Phuong Nguyen**, Round
Rock, TX (US); **Janalee Marie Corato**,
Keller, TX (US)

(73) Assignee: **JMC GLOBAL TECHNOLOGIES I,
L.P.**, Keller, TX (US)

(**) Term: **15 Years**

(21) Appl. No.: **29/598,975**

(22) Filed: **Mar. 30, 2017**

Related U.S. Application Data

(63) Continuation of application No. 13/458,635, filed on
Apr. 27, 2012.

(51) **LOC (11) Cl.** **24-02**

(52) **U.S. Cl.**
USPC **D24/128**

(58) **Field of Classification Search**
USPC D24/127-131, 112, 186; 224/221;
604/179, 231
CPC A61M 5/42; A61M 25/0612; A61M 27/00;
A61M 25/02
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,782,404 A 11/1930 Bowly et al.
2,449,882 A 9/1948 Daniels
3,059,645 A 10/1962 Hasbrouck et al.
4,088,136 A 5/1978 Hasslinger et al.

4,316,461 A 2/1982 Marais et al.
D271,160 S * 11/1983 Sherwin 224/221
4,480,639 A 11/1984 Peterson et al.
4,671,787 A 6/1987 Widman
5,084,026 A 1/1992 Shapiro
5,353,974 A * 10/1994 Maurizio A45F 5/00
224/183
5,395,343 A 3/1995 Iscovich
5,397,639 A 3/1995 Tollini
5,549,567 A * 8/1996 Wolman A61M 25/02
128/DIG. 26
5,690,617 A * 11/1997 Wright A61M 25/02
128/DIG. 26
5,876,371 A 3/1999 Yokoyama et al.
(Continued)

Primary Examiner — David G Muller

(74) *Attorney, Agent, or Firm* — Edwin S. Flores; Daniel
J. Chalker; Chalker Flores, LLP


(57) **CLAIM**

The ornamental design for a line management device for
retaining and positioning wires and tubes, as shown and
described.

DESCRIPTION

FIG. 1 is an isometric view of a line management device for
retaining and positioning wires and tubes showing my new
design.
FIG. 2 is a top plan view thereof;
FIG. 3 is a side elevation view thereof;
FIG. 4 is an opposite side elevation view thereof;
FIG. 5 is an end elevation view thereof;
FIG. 6 is an opposite end elevation view thereof; and,
FIG. 7 is a front view a line management device for retaining
and positioning wires and tubes showing my new design in
operation to retain and position the wires to a call device.
The broken line showing of parts of the drawings is included
for the purpose of illustrating use and environment and
forms no part of the claimed design.

1 Claim, 4 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D424,692	S	5/2000	Monaghan et al.	
6,315,759	B1	11/2001	Peterson	
6,321,957	B1 *	11/2001	Rossi	A01K 27/006 206/811
6,500,154	B1	12/2002	Hakky et al.	
6,526,981	B1	3/2003	Rozier et al.	
6,544,232	B1	4/2003	McDaniel	
7,255,251	B1	8/2007	Smith	
7,413,561	B2 *	8/2008	Raulerson	A61M 25/02 604/174
7,624,480	B2 *	12/2009	Coronel	A61M 25/02 128/DIG. 15
D622,840	S	8/2010	Heitkamp	
7,766,289	B2	8/2010	Newkirk et al.	
8,152,776	B2 *	4/2012	McCluskey	A61M 5/1418 604/178
8,408,436	B2 *	4/2013	Berry	A63B 24/00 224/176
8,834,425	B2 *	9/2014	Bracken	A61L 24/0031 604/174
8,857,434	B2 *	10/2014	Han	A61M 16/0683 128/207.11
9,004,329	B2 *	4/2015	Hsieh	G04G 17/08 224/169
9,878,129	B2 *	1/2018	Larkin	A61M 25/02
2005/0137496	A1	6/2005	Walsh et al.	
2006/0064950	A1	3/2006	Ford et al.	
2009/0105656	A1	4/2009	Schaeffer	
2009/0281502	A1	11/2009	Heitkamp	
2012/0277682	A1	11/2012	Corato et al.	

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7