



US00D818949S

(12) **United States Design Patent**  
**Dunkin et al.**

(10) **Patent No.:** **US D818,949 S**

(45) **Date of Patent:** **\*\* May 29, 2018**

(54) **BATTERY**

(71) Applicant: **Ridge Tool Company**, Elyria, OH (US)

(72) Inventors: **Jon R. Dunkin**, Elyria, OH (US);  
**Michael J. Rutkowski**, Locust Grove,  
VA (US)

(73) Assignee: **Ridge Tool Company**, Elyria, OH (US)

(\*\*) Term: **15 Years**

(21) Appl. No.: **29/599,320**

(22) Filed: **Mar. 31, 2017**

(51) **LOC (11) Cl.** ..... **13-02**

(52) **U.S. Cl.**  
USPC ..... **D13/103**

(58) **Field of Classification Search**  
USPC ..... D13/102-104, 110, 118-121, 184, 199;  
D14/356, 432

CPC ..... Y02E 60/12; Y02E 60/122; Y02E 60/124;  
Y02E 60/50; H01M 10/4257; H01M  
10/0436; H01M 10/48; H01M 10/44;  
H01M 10/46; H01M 10/482; H01M  
10/465; H01M 2/02; H01M 2/022; H01M  
2/0202; H01M 2/0207; H01M 2/0212;  
H01M 2/1061; H01M 2/1022; H01M  
2/1055; H01M 2/1066; H01M 2/105;  
H01M 2/204; H02J 7/00; H02J 7/0003;  
H02J 7/0011; H02J 7/0013; H02J 7/0054;  
H02J 7/0055; H02J 7/0057; H02J  
2007/0062

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

D528,975 S \* 9/2006 Chi ..... D13/103  
D547,264 S \* 7/2007 Kondo ..... D13/103

D597,482 S \* 8/2009 Kondo ..... D13/103  
D682,195 S \* 5/2013 Aglassinger ..... D13/103  
D699,672 S \* 2/2014 Kosugi ..... D13/103  
D700,138 S \* 2/2014 Walz ..... D13/103  
D702,630 S \* 4/2014 Tinius ..... D13/103  
D766,175 S \* 9/2016 Tsiopanos ..... D13/103  
D773,389 S \* 12/2016 Miller ..... D13/103  
2009/0229842 A1 \* 9/2009 Gray ..... H01M 2/1055  
173/20  
2013/0196203 A1 \* 8/2013 Wackwitz ..... B25F 5/00  
429/96

\* cited by examiner

*Primary Examiner* — Rosemary K Tarcza

*Assistant Examiner* — Christy Nemeth

(74) *Attorney, Agent, or Firm* — Mark E. Bandy; Rankin,  
Hill & Clark LLP



(57) **CLAIM**

The ornamental design for a battery, as shown and described.

**DESCRIPTION**

FIG. 1 is a front perspective view of a battery;  
FIG. 2 is a rear perspective view thereof;  
FIG. 3 is a front view thereof;  
FIG. 4 is a rear view thereof;  
FIG. 5 is a right side view thereof;  
FIG. 6 is a left side view thereof;  
FIG. 7 is a top view thereof; and,  
FIG. 8 is a bottom view thereof.  
The broken lines in the drawings are for the purpose of  
illustrating portions of the battery that form no part of the  
claimed design.

**1 Claim, 8 Drawing Sheets**






FIG. 1




FIG. 2






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7






FIG. 8