



US00D820777S

(12) **United States Design Patent**
Robbins

(10) **Patent No.:** **US D820,777 S**
(45) **Date of Patent:** **** Jun. 19, 2018**

- (54) **TIRE TREAD**
- (71) Applicant: **COOPER TIRE & RUBBER COMPANY**, Findlay, OH (US)
- (72) Inventor: **Bryan D. Robbins**, Findlay, OH (US)
- (73) Assignee: **COOPER TIRE & RUBBER COMPANY**, Findlay, OH (US)
- (**) Term: **15 Years**
- (21) Appl. No.: **29/578,522**
- (22) Filed: **Sep. 22, 2016**
- (51) **LOC (11) Cl.** **12-15**
- (52) **U.S. Cl.**
USPC **D12/600**
- (58) **Field of Classification Search**
USPC D12/539, 540, 544, 574, 575, 579, 580, 600, 612, 614, 616, 618, 620, 622, 624, 626, 628, 630, 632, 634, 636, 638, 640, 642, 644, 646, 648, 650, 652, 654, 656, 658, 660, 662, 664, 666, 668, 670, 672, 674, 676, 678, 680, 682, 684, 686, 688, 690, 692, 694, 696, 698, 700, 702, 704, 706, 708, 710, 712, 714, 716, 718, 720, 722, 724, 726, 728, 730, 732, 734, 736, 738, 740, 742, 744, 746, 748, 750, 752, 754, 756, 758, 760, 762, 764, 766, 768, 770, 772, 774, 776, 778, 780, 782, 784, 786, 788, 790, 792, 794, 796, 798, 800, 802, 804, 806, 808, 810, 812, 814, 816, 818, 820, 822, 824, 826, 828, 830, 832, 834, 836, 838, 840, 842, 844, 846, 848, 850, 852, 854, 856, 858, 860, 862, 864, 866, 868, 870, 872, 874, 876, 878, 880, 882, 884, 886, 888, 890, 892, 894, 896, 898, 900, 902, 904, 906, 908, 910, 912, 914, 916, 918, 920, 922, 924, 926, 928, 930, 932, 934, 936, 938, 940, 942, 944, 946, 948, 950, 952, 954, 956, 958, 960, 962, 964, 966, 968, 970, 972, 974, 976, 978, 980, 982, 984, 986, 988, 990, 992, 994, 996, 998, 1000
CPC ... B60C 11/03; B60C 11/0306; B60C 11/0311
See application file for complete search history.

- D628,958 S 12/2010 Fleckner
- D634,266 S 3/2011 Shan et al.
- D638,352 S 5/2011 Osaka
- D642,512 S 8/2011 Jacobs
- D644,597 S 9/2011 Lucas
- D682,190 S * 5/2013 Uphouse D12/600
- D683,301 S 5/2013 Kang
- D684,525 S 6/2013 Kuwano
- D687,765 S 8/2013 Kuwano et al.
- D713,329 S * 9/2014 Dixon D12/579
- D727,248 S 4/2015 Reim et al.
- D729,150 S 5/2015 Jacobs et al.
- D731,404 S 6/2015 Jacobs
- D732,467 S * 6/2015 Schimmoeller D12/600
- D736,145 S * 8/2015 Jacobs D12/594
- D736,694 S 8/2015 Jacobs
- D739,815 S 9/2015 Kim

(Continued)

Primary Examiner — Robert M. Spear
(74) *Attorney, Agent, or Firm* — Fay Sharpe LLP

(57) **CLAIM**

The ornamental design for a tire tread, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire tread of the present application;
FIG. 2 is a front view thereof;
FIG. 3 is a side view thereof;
FIG. 4 is an enlarged partial perspective view thereof; and,
FIG. 5 is an enlarged partial front view thereof.
The broken lines and the region defining the inner bead and that portion of the sidewall between the broken lines form no part of the claimed tire tread design, and are included for the purpose of illustrating the full tire. The tread pattern is understood to uniformly repeat throughout the circumference of the tire. The other side view of the tire is identical to the illustrated side view.

1 Claim, 5 Drawing Sheets

- (56) **References Cited**
U.S. PATENT DOCUMENTS
- D296,684 S * 7/1988 Krupa D12/579
- D325,186 S 4/1992 Pulte, Jr.
- D365,061 S 12/1995 Lissan et al.
- D390,516 S 2/1998 Lissan et al.
- D402,935 S * 12/1998 Oliver D12/594
- D445,377 S 7/2001 Fantanzo et al.
- D495,293 S * 8/2004 Tahira D12/600
- D495,294 S 8/2004 Ochi et al.
- D514,059 S 1/2006 Dixon
- D578,059 S 10/2008 Fujita
- D578,956 S 10/2008 Dixon et al.
- D594,815 S * 6/2009 Reim D12/579
- D610,071 S 2/2010 Song
- D626,501 S 11/2010 Cazin-Bourguignon et al.



(56)

References Cited

U.S. PATENT DOCUMENTS

D748,044 S *	1/2016	Schuessler	D12/580
D748,047 S *	1/2016	Schuessler	D12/594
D753,582 S	4/2016	Matsuda	
D754,592 S *	4/2016	Tian	D12/600
D756,903 S	5/2016	Sareen	
D763,177 S *	8/2016	Chen	D12/579
D784,918 S *	4/2017	Liu	D12/594
2014/0360641 A1 *	12/2014	Jacobs	B60C 11/1307 152/209.21

* cited by examiner



FIG. 1



FIG. 2




FIG. 3



FIG. 4




FIG. 5