



US00D824523S

(12) **United States Design Patent** (10) **Patent No.:** **US D824,523 S**
Paoli et al. (45) **Date of Patent:** **** Jul. 31, 2018**

(54) **SENSOR**

(56)

References Cited

(71) Applicant: **RYTHM**, Paris (FR)

U.S. PATENT DOCUMENTS

(72) Inventors: **Alix Paoli**, Paris (FR); **Léa Kobeli**, San Francisco, CA (US); **Charlie Nghiem**, San Francisco, CA (US); **Quentin Soulet de Brugière**, Paris (FR); **Hugo Mercier**, Paris (FR)

D366,732 S * 1/1996 Gregg D29/108
D567,219 S * 4/2008 Viduya D14/205
D693,459 S * 11/2013 Prentice D24/110.1
D704,326 S * 5/2014 Formica D24/110.1
D724,585 S * 3/2015 Choo D14/372
D730,352 S * 5/2015 Chow D14/372
D747,495 S * 1/2016 Attal D24/186
D776,286 S * 1/2017 Min D24/187
2009/0066607 A1 * 3/2009 Yasuda G02B 27/0176
345/8
2015/0257674 A1 * 9/2015 Jordan A61B 5/0006
600/383

(73) Assignee: **RYTHM**, Paris (FR)

(**) Term: **15 Years**

(Continued)

(21) Appl. No.: **29/581,373**

(22) Filed: **Oct. 18, 2016**

OTHER PUBLICATIONS

(30) **Foreign Application Priority Data**

Rythm Dreem headband promises you'll sleep better wearing it, posted Mar. 3, 2016, [online], [site visited Nov. 30, 2017]. Available from Internet, URL: <https://www.wearable.com/meet-the-boss/rythm-dreem-headband>.*

Apr. 19, 2016 (EM) 003073899-0001

(51) **LOC (11) Cl.** **24-01**

(52) **U.S. Cl.**

USPC **D24/186**

(58) **Field of Classification Search**

USPC D24/165–168, 185–187, 107, 110.1, 174,
D24/231, 200; D10/46, 47, 70, 98;
D14/205, 206, 223, 224, 372, 496, 432,
D14/371, 125, 126, 129, 299;
D16/300–342; 351/158, 153, 144;
345/7–9, 905; 455/344; 348/115, 53,
348/121, 739

CPC ... A61B 5/6824; A61B 5/6831; A61B 5/6832;
A61B 5/02405; A61B 5/02411; A61B
5/02427; A61B 5/02438; A61B 5/6803;
A61B 5/6814; A61B 2562/0204; G01T
1/00; G01T 1/02; G01T 1/15; G01T 1/26;
G01T 1/24

See application file for complete search history.

Primary Examiner — Anhdao Doan

Assistant Examiner — Mary Malley

(74) *Attorney, Agent, or Firm* — Volpe and Koenig, P.C.

(57)

CLAIM

The ornamental design for sensor, as shown and described.

DESCRIPTION

FIG. 1 is a rear perspective view of the sensor according to our design;
FIG. 2 is a front view of the sensor of FIG. 1;
FIG. 3 is a rear view of the sensor of FIG. 1;
FIG. 4 is a left side view of the sensor of FIG. 1, the right side being a mirror image thereof;
FIG. 5 is a top plan view of the sensor of FIG. 1;
FIG. 6 is a bottom view of the sensor of FIG. 1; and,
FIG. 7 is a three-quarter isometric view of the sensor of FIG. 1.

1 Claim, 7 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2017/0135638 A1* 5/2017 Gal A61B 5/6831
2017/0164903 A1* 6/2017 Soulet De
Brugiere A61B 5/7225

* cited by examiner



FIG. 1



FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6



FIG. 7