



US00D828555S

(12) **United States Design Patent** (10) **Patent No.:** **US D828,555 S**
Anderson et al. (45) **Date of Patent:** **** Sep. 11, 2018**

(54) **SUTURING DEVICE**
(71) Applicant: **Dura Tap LLC**, Wayne, PA (US)
(72) Inventors: **David Greg Anderson**, Moorestown, NJ (US); **Mark F. Kurd**, Bryn Mawr, PA (US); **Jay Tapper**, Wayne, PA (US); **Jens Johnson**, Austin, TX (US)
(73) Assignee: **Dura Tap LLC**, Wayne, PA (US)

(**) Term: **15 Years**

(21) Appl. No.: **29/613,283**

(22) Filed: **Aug. 9, 2017**

(51) **LOC (11) Cl.** **24-02**

(52) **U.S. Cl.**
USPC **D24/145**

(58) **Field of Classification Search**
USPC D24/145-147, 133
CPC A61B 17/0469; A61B 17/0483; A61B 17/0482; A61B 17/06166; A61B 2017/2929; A61B 2017/06176
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | | | |
|--------------|------|---------|----------|-------|--------------|
| 5,104,381 | A * | 4/1992 | Gresl | | A61B 17/3496 |
| | | | | | D24/146 |
| 5,364,410 | A * | 11/1994 | Failla | | A61B 17/0469 |
| | | | | | 606/135 |
| D708,741 | S * | 7/2014 | Harrison | | D24/145 |
| 8,974,494 | B2 * | 3/2015 | Paulk | | A61B 17/0469 |
| | | | | | 606/104 |
| D737,971 | S * | 9/2015 | Wagner | | D24/145 |
| D815,739 | S * | 4/2018 | Anderson | | D24/145 |
| 9,931,111 | B2 * | 4/2018 | Chu | | A61B 17/0469 |
| 2004/0127915 | A1 * | 7/2004 | Fleenor | | A61B 17/0469 |
| | | | | | 606/144 |

| | | | | | |
|--------------|------|---------|----------|-------|---------------|
| 2007/0049966 | A1 * | 3/2007 | Bonadio | | A61B 17/00234 |
| | | | | | 606/206 |
| 2016/0317144 | A1 * | 11/2016 | Popovici | | A61B 17/0469 |
| 2017/0020514 | A1 * | 1/2017 | Paulk | | A61B 17/0469 |
| 2018/0028178 | A1 * | 2/2018 | Murray | | A61B 17/0482 |

* cited by examiner

Primary Examiner — Wan Laymon

(74) *Attorney, Agent, or Firm* — Rankin, Hill & Clark LLP


(57) **CLAIM**

The ornamental design for a suturing device, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a suturing device with a plunger in an extended position;
FIG. 2 is a perspective view thereof with the plunger in a depressed position;
FIG. 3 is a right side elevation view thereof;
FIG. 4 is a left side elevation view thereof;
FIG. 5 is a front elevation view thereof;
FIG. 6 is a rear elevation view thereof;
FIG. 7 is a top plan view thereof;
FIG. 8 is a bottom plan view thereof;
FIG. 9 is a perspective view of an alternative suturing device with a plunger in an extended position;
FIG. 10 is a perspective view thereof with the plunger in a depressed position;
FIG. 11 is a right side elevation view thereof;
FIG. 12 is a left side elevation view thereof;
FIG. 13 is a front elevation view thereof;
FIG. 14 is a rear elevation view thereof;
FIG. 15 is a top plan view thereof; and,
FIG. 16 is a bottom plan view thereof.

1 Claim, 8 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13



FIG. 14




FIG. 15




FIG. 16