

US00D833047S

(12) **United States Design Patent** (10) **Patent No.:** **US D833,047 S**
Giambanco (45) **Date of Patent:** **** Nov. 6, 2018**

(54) **WEARABLE LED DEVICE**

(71) Applicant: **Jack Giambanco**, Brooklyn, NY (US)

(72) Inventor: **Jack Giambanco**, Brooklyn, NY (US)

(**) Term: **15 Years**

(21) Appl. No.: **29/586,122**

(22) Filed: **Nov. 30, 2016**

(51) **LOC (11) Cl.** **26-02**

(52) **U.S. Cl.**
USPC **D26/39**

(58) **Field of Classification Search**

USPC D26/37, 38, 39, 46, 51
CPC F21L 2003/00; F21L 4/00; F21L 4/005;
F21L 4/02; F21L 4/025; F21L 4/027;
F21L 4/04; F21L 4/08; F21L 2005/00;
F21L 7/00; F21L 11/00; F21L 13/00;
F21L 13/04; F21L 13/08; F21L 14/02;
F21L 17/00; F21L 19/00

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D448,505 S * 9/2001 Dalton D26/37
D498,553 S * 11/2004 Lee D26/37
D544,388 S * 6/2007 Chisholm D10/114.2
D567,414 S * 4/2008 Schnell D26/37
D583,491 S * 12/2008 Siemers D26/37
D593,238 S * 5/2009 Allen D26/37
D594,148 S * 6/2009 Heselden D26/37

(Continued)

Primary Examiner — Karen E Kearney

Assistant Examiner — Carissa C Fitts

(74) *Attorney, Agent, or Firm* — Sonya C. Harris;
Invention Services


(57) **CLAIM**

The ornamental design for the wearable LED device, as shown and described.

DESCRIPTION

FIG. 1 is a front elevational view of my design;
FIG. 2 is a right side elevational view of my design;
FIG. 3 is a left side elevational view of my design;
FIG. 4 is a top elevational view of my design;
FIG. 5 is a rear elevational view of my design;
FIG. 6 is a bottom elevational view of my design;
FIG. 7 is a bottom front right perspective view of my design;
FIG. 8 is a top front left side perspective view of my design;
FIG. 9 is a front elevational partially exploded view of my design, illustrating removal of the pull-tab, which activates the LED for illumination;
FIG. 10 is a top right front partially exploded perspective view of my design, illustrating removal of the pull-tab, which activates the LED for illumination;
FIG. 11 is a bottom left front partially exploded perspective view of my design, illustrating removal of the pull-tab, which activates the LED for illumination;
FIG. 12 is a bottom right front exploded perspective view of my design, illustrating components of the device;
FIG. 13 is a top left front exploded perspective view of my design, illustrating components of the device;
FIG. 14 is a rear elevational view of the base housing component of my design;
FIG. 15 is a front elevational view of the base housing component of my design;
FIG. 16 is a bottom left front perspective view of the base housing component of my design;
FIG. 17 is a top right front perspective view of the base-housing component of my design;
FIG. 18 is a rear elevational view of the cap-housing component of my design;
FIG. 19 is a front elevational view of the cap-housing component of my design; and,
FIG. 20 is a top left rear perspective view of the cap-housing component of my design.

1 Claim, 12 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D605,794 S *	12/2009	Engebrigtsen	D26/37
D612,963 S *	3/2010	Oki	D26/37
D619,281 S *	7/2010	Toomey	D26/37
D622,879 S *	8/2010	Kotsis	D26/37
D645,191 S *	9/2011	Krause	D26/37
D739,059 S *	9/2015	Trauterer	D26/37
D751,741 S *	3/2016	Watson	D26/37
D765,294 S *	8/2016	Li	D26/37
D768,321 S *	10/2016	Inskeep	D26/37
2017/0208790 A1 *	7/2017	Dyer	A01K 97/02

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 10




FIG. 9




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 19




FIG. 20




FIG. 18