



US00D833381S

(12) **United States Design Patent**
Fujioka

(10) **Patent No.:** **US D833,381 S**

(45) **Date of Patent:** **** Nov. 13, 2018**

- (54) **TIRE**
- (71) Applicant: **Toyo Tire & Rubber Co., Ltd.**,
Itami-shi, Hyogo (JP)
- (72) Inventor: **Tsuyoshi Fujioka**, Itami (JP)
- (73) Assignee: **TOYO TIRE & RUBBER CO., LTD.**,
Osaka (JP)

- D774,447 S * 12/2016 Mathis D12/605
- D776,046 S * 1/2017 Dixon D12/605
- D779,425 S * 2/2017 Scheifele D12/605
- D783,519 S * 4/2017 Fujioka D12/605
- D784,250 S * 4/2017 Kuwano D12/600
- D786,186 S * 5/2017 Kuwano D12/600
- D809,453 S * 2/2018 Sato D12/604
- D810,674 S * 2/2018 Itoi D12/605
- D815,591 S * 4/2018 Rogers D12/605
- D816,598 S * 5/2018 Cerny D12/602

(Continued)

(**) Term: **15 Years**

(21) Appl. No.: **29/619,192**

(22) Filed: **Sep. 27, 2017**

(30) **Foreign Application Priority Data**

May 31, 2017 (JP) 2017-011743

(51) **LOC (11) Cl.** **12-15**

(52) **U.S. Cl.**
USPC **D12/605**

(58) **Field of Classification Search**
USPC D12/501, 544, 579, 564-565, 570, 574,
D12/581-586, 588-590, 594-596,
D12/599-608; D7/39
CPC ... B60C 27/08; B60C 27/086; B60C 27/0223;
B60C 11/1675; B60C 11/14; B60C 13/00;
B60C 1/00
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- D447,449 S * 9/2001 Guspodin D12/605
- D453,311 S * 2/2002 Guspodin D12/579
- D565,501 S * 4/2008 Lo D12/544
- D663,682 S * 7/2012 Ohara D12/605
- D710,295 S * 8/2014 Bortolet D12/601
- D729,155 S 5/2015 Jacobs
- D756,903 S * 5/2016 Sareen D12/600
- D766,167 S * 9/2016 Chen D12/579

Primary Examiner — Robin V Webster

Assistant Examiner — Rachel A Voorhies

(74) *Attorney, Agent, or Firm* — Sterne, Kessler,
Goldstein & Fox P.L.L.C.

(57) **CLAIM**


The ornamental design for a tire, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of a tire showing the claimed design;
 FIG. 2 is a front view thereof, the rear view being the same;
 FIG. 3 is a top plan view thereof, the bottom plan view being the same;
 FIG. 4 is a right side view thereof, the left side view being the same;
 FIG. 5 is an enlarged view taken along the line 5-5 in FIG. 1;
 FIG. 6 is an enlarged view of the portion between 6-6 and 6'-6' in FIG. 2; and,
 FIG. 7 is a cross-sectional view taken along line 7-7 in FIG. 6.

In the drawings, the broken lines show portions of the tire that form no part of the claimed design. The broken lines immediately adjacent to the sidewall features shown in solid lines represent the boundary of the claim and form no part thereof.

1 Claim, 7 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D820,777 S *	6/2018	Robbins	B60C 11/01
			D12/600
2003/0041939 A1 *	3/2003	Allison	B60C 11/01
			152/209.1

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : D833,381 S
APPLICATION NO. : 29/619192
DATED : November 13, 2018
INVENTOR(S) : Tsuyoshi Fujioka


Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the Title Page

Item (73), please replace "Toyo Tire Rubber Co., Ltd., Osaka (JP)" with --Toyo Tire & Rubber Co., Ltd., Itami-shi, Hyogo (JP)--.

Signed and Sealed this
Nineteenth Day of November, 2019



Andrei Iancu
Director of the United States Patent and Trademark Office