



US00D833381S

(12) **United States Design Patent**  
**Fujioka**

(10) **Patent No.:** **US D833,381 S**

(45) **Date of Patent:** **\*\* Nov. 13, 2018**

(54) **TIRE**  
(71) Applicant: **Toyo Tire & Rubber Co., Ltd.**,  
Itami-shi, Hyogo (JP)  
(72) Inventor: **Tsuyoshi Fujioka**, Itami (JP)  
(73) Assignee: **TOYO TIRE & RUBBER CO., LTD.**,  
Osaka (JP)

D774,447 S \* 12/2016 Mathis ..... D12/605  
D776,046 S \* 1/2017 Dixon ..... D12/605  
D779,425 S \* 2/2017 Scheifele ..... D12/605  
D783,519 S \* 4/2017 Fujioka ..... D12/605  
D784,250 S \* 4/2017 Kuwano ..... D12/600  
D786,186 S \* 5/2017 Kuwano ..... D12/600  
D809,453 S \* 2/2018 Sato ..... D12/604  
D810,674 S \* 2/2018 Itoi ..... D12/605  
D815,591 S \* 4/2018 Rogers ..... D12/605  
D816,598 S \* 5/2018 Cerny ..... D12/602

(Continued)

(\*\*) Term: **15 Years**

*Primary Examiner* — Robin V Webster

*Assistant Examiner* — Rachel A Voorhies

(21) Appl. No.: **29/619,192**

(74) *Attorney, Agent, or Firm* — Sterne, Kessler,  
Goldstein & Fox P.L.L.C.

(22) Filed: **Sep. 27, 2017**

(30) **Foreign Application Priority Data**

May 31, 2017 (JP) ..... 2017-011743

(51) **LOC (11) Cl.** ..... **12-15**

(52) **U.S. Cl.**  
USPC ..... **D12/605**

(58) **Field of Classification Search**  
USPC ..... D12/501, 544, 579, 564–565, 570, 574,  
D12/581–586, 588–590, 594–596,  
D12/599–608; D7/39  
CPC ... B60C 27/08; B60C 27/086; B60C 27/0223;  
B60C 11/1675; B60C 11/14; B60C 13/00;  
B60C 1/00  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D447,449 S \* 9/2001 Guspodin ..... D12/605  
D453,311 S \* 2/2002 Guspodin ..... D12/579  
D565,501 S \* 4/2008 Lo ..... D12/544  
D663,682 S \* 7/2012 Ohara ..... D12/605  
D710,295 S \* 8/2014 Bortolet ..... D12/601  
D729,155 S 5/2015 Jacobs  
D756,903 S \* 5/2016 Sareen ..... D12/600  
D766,167 S \* 9/2016 Chen ..... D12/579

(57) **CLAIM**


The ornamental design for a tire, as shown and described.

**DESCRIPTION**

FIG. 1 is a front perspective view of a tire showing the claimed design;  
FIG. 2 is a front view thereof, the rear view being the same;  
FIG. 3 is a top plan view thereof, the bottom plan view being the same;  
FIG. 4 is a right side view thereof, the left side view being the same;  
FIG. 5 is an enlarged view taken along the line 5-5 in FIG. 1;  
FIG. 6 is an enlarged view of the portion between 6-6 and 6'-6' in FIG. 2; and,  
FIG. 7 is a cross-sectional view taken along line 7-7 in FIG. 6.

In the drawings, the broken lines show portions of the tire that form no part of the claimed design. The broken lines immediately adjacent to the sidewall features shown in solid lines represent the boundary of the claim and form no part thereof.

**1 Claim, 7 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

D820,777 S \* 6/2018 Robbins ..... B60C 11/01  
D12/600  
2003/0041939 A1\* 3/2003 Allison ..... B60C 11/01  
152/209.1

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6






FIG. 7

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : D833,381 S  
APPLICATION NO. : 29/619192  
DATED : November 13, 2018  
INVENTOR(S) : Tsuyoshi Fujioka


Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the Title Page

Item (73), please replace "Toyo Tire Rubber Co., Ltd., Osaka (JP)" with --Toyo Tire & Rubber Co., Ltd., Itami-shi, Hyogo (JP)--.

Signed and Sealed this  
Nineteenth Day of November, 2019



Andrei Iancu  
*Director of the United States Patent and Trademark Office*