

US00D836201S

(12) **United States Design Patent** (10) **Patent No.:** **US D836,201 S**  
**Lee et al.** (45) **Date of Patent:** **\*\* Dec. 18, 2018**

(54) **PART OF BLOOD PRESSURE MEASUREMENT DEVICE**  
(71) Applicant: **Maisense Inc.**, Zhubei (TW)  
(72) Inventors: **Yung-Pin Lee**, Zhubei (TW); **Min-Hao Lee**, Zhubei (TW); **Chia-Hsiu Yeh**, Zhubei (TW)  
(73) Assignee: **MAISENSE INC.**, Zhubei, Hsinchu County (TW)

(\*\*) Term: **15 Years**

(21) Appl. No.: **29/599,638**

(22) Filed: **Apr. 5, 2017**

(30) **Foreign Application Priority Data**

Jan. 25, 2017 (TW) ..... 106300454

(51) **LOC (11) Cl.** ..... **24-02**

(52) **U.S. Cl.**  
USPC ..... **D24/165**

(58) **Field of Classification Search**  
USPC ..... D24/107, 164-168, 186, 231; D9/434, D9/456, 737, 755, 758, 760; 600/300, 600/301  
CPC .... A61B 5/01; A61B 5/02; A61B 5/04; A61B 5/021; A61B 5/022; A61B 5/0205; A61B 5/0402; A61B 5/6824; A61B 5/02141; A61B 5/02125; A61B 5/02007; A61B 2560/0023  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,692,512 A \* 12/1997 Flachslaender ..... A61B 5/0235 600/485  
D567,949 S \* 4/2008 Lash ..... D24/168  
D643,929 S \* 8/2011 DelloStritto ..... D24/165

D733,888 S \* 7/2015 Tuhkanen ..... D24/167  
D744,109 S \* 11/2015 Yoneta ..... D24/186  
D794,806 S \* 8/2017 Kranz ..... D24/186  
D798,170 S \* 9/2017 Toth ..... D10/65  
D800,313 S \* 10/2017 Chang ..... D24/167  
D810,593 S \* 2/2018 Liu ..... D10/70  
2011/0009757 A1\* 1/2011 Sano ..... A61B 5/02141 600/499  
2012/0330169 A1\* 12/2012 Sano ..... A61B 5/02233 600/499  
2014/0350419 A1\* 11/2014 Doi ..... A61B 5/02233 600/499

(Continued)

*Primary Examiner* — Wan Laymon

*Assistant Examiner* — Clint A Samuel

(74) *Attorney, Agent, or Firm* — Muncy, Geissler, Olds & Lowe, P.C.


(57) **CLAIM**

The ornamental design for a part of blood pressure measurement device, as shown and described.

**DESCRIPTION**

FIG. 1 is a first perspective view of a part of blood pressure measurement device showing my new design;  
FIG. 2 is a front view thereof;  
FIG. 3 is a rear front view thereof;  
FIG. 4 is a left side view thereof;  
FIG. 5 is a right side view thereof;  
FIG. 6 is a top view thereof;  
FIG. 7 is a bottom view thereof;  
FIG. 8 is a cross-sectional view taken along Line 8-8 in FIG. 6;  
FIG. 9 is a second perspective view thereof; and,  
FIG. 10 is a third perspective view thereof in an exemplary use.  
The broken lines shown in figures illustrate environmental structures and form no part of the claimed design. The dot-dash lines shown in figures represent boundary lines and form no part of the claimed design.

**1 Claim, 8 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

2016/0157717 A1\* 6/2016 Gaster ..... A61B 5/0444  
600/301  
2017/0188872 A1\* 7/2017 Hughes ..... A61B 5/6832  
2018/0160909 A1\* 6/2018 Damania ..... A61B 5/01  
2018/0206731 A1\* 7/2018 Lee ..... A61B 5/021  
2018/0206736 A1\* 7/2018 Lee ..... A61B 5/0205

\* cited by examiner




FIG.1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG.6




FIG. 7




FIG.8






FIG.9




FIG.10