



US00D837549S

(12) **United States Design Patent**
Buffery

(10) **Patent No.:** **US D837,549 S**
(45) **Date of Patent:** **** Jan. 8, 2019**

- (54) **VEHICLE SEAT**
- (71) Applicant: **Jaguar Land Rover Limited**, Whitley, Coventry (GB)
- (72) Inventor: **Martin Buffery**, Coventry (GB)
- (73) Assignee: **Jaguar Land Rover Limited**, Whitley Coventry (GB)
- (**) Term: **15 Years**
- (21) Appl. No.: **29/603,621**
- (22) Filed: **May 11, 2017**

8,556,222	B2 *	10/2013	Yamada	B60N 2/0705	248/429
D723,821	S *	3/2015	Kondou	D6/356	
D723,824	S *	3/2015	Persson	D6/356	
D771,398	S *	11/2016	Buffery	D6/356	
9,604,549	B2 *	3/2017	Makiguchi	B60N 2/02	
D799,225	S *	10/2017	Callum	D6/356	
D801,065	S *	10/2017	Willis	D6/356	
D804,206	S *	12/2017	Varga	D6/356	
D804,838	S *	12/2017	Blomme	D6/356	
D805,312	S *	12/2017	Varga	D6/356	
D805,313	S *	12/2017	Varga	D6/356	
D808,185	S *	1/2018	Kondo	D6/356	
9,919,620	B2 *	3/2018	Supernavage	B60N 2/015	
2008/0088170	A1 *	4/2008	Kim	B60R 22/00	297/468
2015/0246624	A1 *	9/2015	Furuta	B29C 65/7829	297/344.15

(30) **Foreign Application Priority Data**

- Nov. 11, 2016 (EM) 003458975-0001
- Nov. 11, 2016 (EM) 003458975-0002
- Nov. 11, 2016 (EM) 003458975-0003

(51) **LOC (11) Cl.** **06-01**

(52) **U.S. Cl.**
USPC **D6/356**

(58) **Field of Classification Search**
USPC D6/356, 335-338, 357, 360, 367, 716.4, D6/716.1, 349; D12/400, 345, 190, 195
CPC . B60N 2/00; B60N 2/01; B60N 2/012; B60N 2/02; B60N 2/0292; B60N 2/24; B60N 2/32; B60N 2/34; B60N 2/38; B60N 2/42
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- D365,216 S * 12/1995 Smith D6/356
- D387,914 S * 12/1997 Beermann D6/356
- 7,708,343 B2 * 5/2010 Kayumi B60N 2/99 297/284.9
- 8,474,911 B2 * 7/2013 Parker B60N 2/12 297/311

* cited by examiner

Primary Examiner — Deanna L Pratt

(74) *Attorney, Agent, or Firm* — Wood Herron & Evans LLP

(57) **CLAIM**

The ornamental design for a vehicle seat, as shown and described.

DESCRIPTION

FIG. 1 is a front left perspective view of a seat for a vehicle according to the present invention.
 FIG. 2 is a front right perspective view of the vehicle seat shown in FIG. 1.
 FIG. 3 is a rear left perspective view thereof.
 FIG. 4 is a rear right perspective view thereof.
 FIG. 5 is a front view thereof.
 FIG. 6 is a rear view thereof.
 FIG. 7 is a left side view thereof.
 FIG. 8 is a right side view thereof; and,
 FIG. 9 is a top view thereof.

1 Claim, 9 Drawing Sheets






FIG. 1



FIG. 2




FIG. 3



FIG. 4



FIG. 5



FIG. 6




FIG. 7



FIG. 8




FIG. 9